

INFUSE 2024, August 8, 2024

Company: Blue Laser Fusion, SAM UEI: NQP9Y1JRFBE5

Title: High Energy Pulsed Laser Amplification Using Optical Enhancement Cavities

Abstract:

Blue Laser Fusion, Inc. is a start-up, small business developing a novel high power laser concept that enables consideration of new target materials and structures. The Blue Laser Fusion laser concept is achieved through the implementation of a large-scale high finesse cavity, also known as an optical enhancement cavity, that coherently stacks pulses temporally separated in time, resulting in short pulse generation with energies on the order of kilojoules with up to a 10 Hz repetition rate, and an estimated 40% wall-plug efficiency. While the technique has been demonstrated at small cavity lengths, we seek to build cavities on the order of 150 m, which require high precision diagnostic tools and controls as well as specialized optical coatings to amplify the laser light with almost no loss. Professor Rana Adhikari, director of the 40m laser lab at Caltech, has decades of experience developing diagnostics, controls, and high reflectivity optics for large-scale laser cavities for the detection of gravitational waves. In this work, Professor Adhikari will evaluate new diagnostics and controls for the pulsed-laser regime, that we will then implement in an optical enhancement cavity optimized for high-energy laser generation suitable for inertial fusion energy application.

Company PI: Dr. Trevor Cohen

Company e-mail: tcohen@bluelaserfusion.com

Institution: California Institute of Technology

Institution PI: Rana Adhikari, rana@caltech.edu





INFUSE 2024, August 8, 2024

Company: Commonwealth Fusion Systems, SAM UEI: FLSJGUF7BGS1

Title: SOLPS-derived separatrix operating space scalings for informing SPARC integrated power exhaust

scenarios

Abstract:

Commonwealth Fusion System (CFS) is currently building the SPARC tokamak outside of Boston, MA. It will demonstrate commercially relevant net energy. SPARC is designed to operate in a highly-dissipative edge plasma regime to mitigate heat flux on its divertor targets through controlled impurity seeding. This collaboration with Oak Ridge National Laboratory (ORNL) will investigate the impact of these impurities on plasma performance by leveraging SOLPS multi-physics modeling capabilities at ORNL. ORNL researchers will produce light-weight scalings from SOLPS simulation data for use by CFS towards SPARC scenario planning and control.

Company PI: Dr. Thomas Eich

Company e-mail: teich@cfs.energy

Institution: ORNL

Institution PI: Bart Lomanowski, lomanowskiba@ornl.gov





INFUSE 2024, August 8, 2024

Company: Commonwealth Fusion Systems, SAM UEI: FLSJGUF7BGS1

Title: In situ Elemental Analysis of Fluoride Molten Salt Using Laser Induced Breakdown Spectroscopy (LIBS)

Abstract:

This INFUSE project seeks to demonstrate the viability of using Laser Induced Breakdown Spectroscopy (LIBS) to quantify metallic and nonmetallic impurities in fluoride molten salts at the sensitivity required for service on ARC. Impurities in salt can significantly alter its chemistry resulting in operations impacts. Therefore, an accurate, real-time and in situ quantification methodology will support safe and successful operation of a fusion power plant using molten salt blankets. The project, led by ORNL, will leverage the laboratory expertise in real-time monitoring and the existing capabilities to measure Cr, Fe, O and H elements in FLiNaK. It will initially focus on utilizing single-pulse LIBS and subsequently explore double-pulse LIBS to achieve the desired sensitivity levels.

Company PI: Dr. Alexi Khechfe

Company e-mail: akhechfe@cfs.energy

Institution: ORNL

Institution PI: Hunter Andrews, andrewshb@ornl.gov





INFUSE 2024, August 8, 2024

Company: Electric Power Research Institute, Inc., SAM UEI: JBV2SMLRBK29

Title: Building a Tritium Facility Operating Experience Body of Knowledge to Support Commercial Fusion Power Plant Safety Case Development and Licensing

Abstract:

The production and use of tritium in fusion energy systems represents a potential radiological hazard requiring evaluation for ensuring adequate protection of workers, the public, and environment. Tritium is produced naturally in small quantities in the upper atmosphere via cosmic radiation interactions with nitrogen. Tritium is also present in nuclear and industrial facilities, both as a nuisance contaminant in the primary coolants of nuclear reactors and as a valued radioisotope used in lighting applications (e.g., emergency exit signs) and in medical diagnostics. Decades of tritium production and management for national defense have established a wealth of experience and documentation on the Savannah River Site. However, due to its association with national defense programs, the US commercial fusion industry and cognizant regulatory authorities have limited access to this knowledge base. This data is controlled under a classification program and difficult to access, especially for those in the private sector. A substantial element of this project is to invest in the effort required to extract this information and have it cleared for public release in the form of a publicly available EPRI technical report.

The proposed work seeks to leverage experts at the DOE Savannah River National Laboratory (SRNL) and the National Nuclear Security Administration (NNSA) Tritium Facilities for the review, identify, collect, organize, and summarize historical tritium handling operating experience, lessons learned, and associated safety analysis information relevant in order to establish a Tritium Facility Operating Experience Body of Knowledge. This resource will be made publicly available and can serve as a starting point for a living, expandable knowledge base capturing relevant operating experience and lessons learned from private and public sector sources in the U.S. and internationally. It is anticipated that this work will also generate a standard template for soliciting and providing tritium operating experience data going forward.

Company PI: Dr. Andrew Sowder

Company e-mail: asowder@epri.com

Institution: SRNL

Institution PI: Luke Olson, luke.olson@srnl.doe.gov





INFUSE 2024, August 8, 2024

Company: ExoFusion, SAM UEI: G1ZWNLDVCSK4

Title: Testing Novel Liquid Metal PFC compositions

Abstract:

The primary goal of this proposal is to perform the experimental testing of a novel class of liquid metal plasma-facing component (LM PFCs) candidate materials using the facilities at Penn State University's Radiation Surface Science and Engineering Laboratory (RSSEL). New alloys will have properties that have a qualitative similarity to SnLi, but are quantitatively greatly improved: alloys will have low Z sputtering, considerably lower vapor pressure and ability to operate at considerably higher temperature. In view of the extreme challenges faced by PFCs in an FPP, and the need for both good PFC operation and excellent core plasma conditions, LMs with the highly advantageous properties described here might be crucial to the progress of magnetic fusion. Experimental results will be fit to models for segregation and thermal sputtering so the properties can be more readily extrapolated.

Company PI: Dr. Michael Kotschenreuther

Company e-mail: mtk@fusionenergyassociates.com

Institution: Penn State University

Institution PI: Martin Nieto-Perez, mnieto@psu.edu





INFUSE 2024, August 8, 2024

Company: Focused Energy, Inc., SAM UEI: 1184117040000

Title: Mitigation of Cross Beam Energy Transfer and Hot Electrons by Laser Spectral Bandwidth

Abstract:

The company Focused Energy (FE) is pursuing the proton fast ignition approach for commercial laser-driven inertial fusion energy. Proton fast ignition separates the assembly phase of high-density inertial fusion fuel from its subsequent ignition phase with a proton beam, which provides higher fusion gains and more robust implosions. The fuel compression is achieved by a spherically distributed configuration of high-energy, nanosecond laser beams. A key scientific risk in laser-driven fusion is the excitation of laser-plasma instabilities (LPI), which can reduce energy coupling, compromise drive uniformity, and might affect the compression of the target because of hot electron preheating. In this INFUSE project FE will partner with leading LPI experts at the University of Rochester (UR) for performing LPI simulations for FE's target compression design. The project will use state of-the-art LPI simulation codes to investigate various LPI mechanisms and hot electron generation and their mitigation by applying lasers with broad spectral bandwidth. LPI is a significant issue for direct drive and the UR modeling capability and their world's leading experts in direct-drive LPI simulations will help FE in exploring LPI mitigation techniques, especially the use of broad bandwidth laser light. The outcome will inform FE on the requirements for the suppression of LPI, which then will feedback on the design of the laser system.

Company PI: Dr. Linh Nguyen

Company e-mail: linh.nguyen@focused-energy.world

Institution: Univ. of Rochester

Institution PI: Arnaud Colaïtis, acol@lle.rochester.edu





INFUSE 2024, August 8, 2024

Company: Focused Energy, Inc, SAM UEI: PNHZTNGJKA45

Title: Tritium Handling System Assessment for Proton Fast Ignition

Abstract:

The handling of tritium is an important issue for any deuterium-tritium (DT) based fusion approach. While other advanced fuels may have some advantages, DT is the only fuel to have demonstrated a burning plasma, ignition, and gain > 1 in laser fusion experiments on the National Ignition Facility (NIF) laser. In order to take the physics results from NIF and move to the high gain (~ 100) needed for a power plant, Focused Energy, Inc is developing proton fast ignition. In proton fast ignition, two sets of laser drive the target – the first set of lasers compresses the fuel and the second set ignites the fuel. This study brings together the expertise on tritium and tritium handling from Savannah River National Laboratory with the reactor chamber and target physics expertise from Focused Energy, Inc. to assess the tritium handling system needed for proton fast ignition.

Company PI: Jim Gaffney

Company e-mail: jim.gaffney@focused-energy.world

Institution: SRNL

Institution PI: Alex Somers, alex.somers@srnl.doe.gov





INFUSE 2024, August 8, 2024

Company: General Atomics, SAM UEI: TVRYQ3N3B8H5

Title: Developing Matter Injection Technologies for Fusion Power Applications

Abstract:

Matter injection technology that has been qualified for continuous, long-term operation will be a critical enabling technology for power-producing fusion pilot plant (FPP) devices. An FPP must be capable of running continuously for a year or more without maintenance to compete with existing power plant technologies. That level of continuous operation necessitates over 1,000 times greater reliability than existing fusion devices, which typically pulse for less than an hour. Matter injection encompasses both continuous high-speed injection of small, cryogenically frozen fuel pellets, and for tokamak-based FPP's, single-shot injection of large pellets for rapid emergency shutdown of the fusion plasma. This project will address two aspects of the fusion matter injection problem. First, from the standpoint of technology development, it will address key issues in the design of an FPP-class fueling centrifuge, which holds promise as a highly desirable steady-state matter injection technology. Second, from the standpoint of industrialization, it will develop the design for an industrial-scale fusion matter injection manufacturing and qualification center. This project links leading United States national laboratory expertise with private industry to develop and industrialize fusion matter injection technology so that it will not constrain future FPP development.

Company PI: Dr. Nicholas Eidietis

Company e-mail: eidietis@fusion.gat.com

Institution: ORNL

Institution PI: Steve Meitner, meitnersj@ornl.gov





INFUSE 2024, August 8, 2024

Company: General Atomics, SAM UEI: TVRYQ3N3B8H5

Title: Metal "Film" Pump for Direct Internal Recycling of Fusion Fuel

Abstract:

This research aims to identify the best performing materials for the development of a metal film pump for selective separation of deuterium and tritium from a mix of gases. A metal film pump is a critical subsystem needed to enable the direct internal recycling (DIR) of tritium in a fusion power plant. Unlike conventional metal foil pumps, the film pumps General Atomics (GA) develops are at least one hundred times thinner. A film pump is advantageous; it facilitates a faster diffusion of gas and can be grown using established techniques. GA's fabrication method assures ultra-clean interfaces, which are fundamental to hydrogen absorption, and allows comixing dopants that increase gas permeation selectivity and help mitigate hydrogen embrittlement effects. Idaho National Laboratory is partnering with GA to test deuterium superpermeation properties and monitor material property changes on GA's film by subjecting it to realistic operational temperature and pressure conditions. For fusion power plants, the DIR concept has the potential to extract unused deuterium and tritium directly from the fuel exhaust of the reactor and direct them back into the gas distribution cycle, bypassing the complex and expensive tritium recovery plant (TRP). If successful, this could ease the burden on the TRP, thus reducing capital cost and onsite tritium inventory by a factor of ~400%, increasing safety, and easing the regulatory requirements. It could also reduce the cost to purchase, produce, and store tritium for future fusion power plants.

Company PI: Dr. Carlos Monton

Company e-mail: carlos.monton@ga.com

Institution: INL

Institution PI: Dr. Masashi Shimada, masashi.shimada@inl.gov





INFUSE 2024, August 8, 2024

Company: Kyoto Fusioneering America Ltd., SAM UEI: PRZRFCLTKSX5

Title: Isotopic Characterization of Li-6-enriched Lithium-Lead Samples under Neutron Irradiation

Abstract:

Lithium-lead (Li-Pb) is one of the leading candidate breeder materials for fusion blanket concepts. To date, most research and development on these materials has been with lithium in its natural isotopic state. Lithium-6 (Li-6) is the isotope of significance for tritium production thanks to its higher neutron absorption cross-section, but the abundance of Li-6 in natural lithium is only 7.8%, with lithium-7 (Li7) comprising the remainder. To achieve a desirable tritium-breeding ratio (TBR) in candidate breeder materials, it is envisioned that higher Li-6 content is needed. However, Li-6 is presently unavailable or at least very limited for commercial purposes, due to the lack of an environmentally acceptable process to make it. Opportunely, there is a U.S. stockpile to which Idaho National Laboratory (INL) can gain access for civilian research endeavors.

This project investigates the behavior of various isotopic compositions of Li-6-enriched liquid lithiumlead (Li-Pb) samples. Over 12 months, we will demonstrate comprehensive techniques to characterize the Li-6/Li-7 isotope ratio in samples in a composition and form to be ready for irradiation. We will assess methods to measure bred tritium, focusing on detecting very low tritium concentrations in LiPb samples using the best available techniques. The resulting samples from this project will mark the first preparation of a relevant breeder composition—with varying ratios of enriched lithium—for a fusion power plant (FPP). This project will also lay the groundwork for future collaboration between Kyoto Fusioneering and INL, which includes irradiation of these samples, but also more in-depth characterization of Li-isotope-ratio measurement, investigation of benchmarks between different techniques for tritium quantification at low concentrations, and potentially to apply the lessons learned to other Li-based breeder materials, such as liquid lithium and FLiBe (lithium-beryllium-fluoride) molten salts.

Company PI: Mr. Chris Dorn

Company e-mail: c.dorn@kyotofusioneering.com

Institution: INL

Institution PI: Chase Taylor, chase.taylor@inl.gov





INFUSE 2024, August 8, 2024

Company: Marathon Fusion, SAM UEI: LF2YSKDB6HL1

Title: Testing of Engineered Membranes in Fusion-Relevant Metal Foil Pumps

Abstract:

The Metal Foil Pump offers a means to rapidly separate hydrogen isotopes from the exhaust gases of a fusion reactor, reducing tritium inventories by a significant factor while also leading to substantial decreases in the cost of reactor tritium processing systems. Recent work has demonstrated record performance in new materials used for the pump's separation membrane, but these materials have been tested in a limited range of experimental conditions. This project aims to characterize membrane performance under conditions representative of planned fusion devices, increasing the technology readiness level of this component and accelerating the deployment of metal foil pumps onto a timeline consistent with the decadal vision for the first pilot plants on the grid.

Company PI: Adam Rutkowski

Company e-mail: adam@marathonfusion.com

Institution: Colorado School of Mines

Institution PI: Dr. Colin Wolden, cwolden@mines.edu





INFUSE 2024, August 8, 2024

Company: Realta Fusion Inc., SAM UEI: MVSHELKP1GZ1

Title: Are Magnetohydrodynamic Forces Low Enough to Enable Single Coolant Lead Lithium Blankets in Tandem Mirror Reactors?

Abstract:

Realta Fusion is an early-stage fusion company commercializing tandem mirror fusion reactors. A key component of the fusion reactor is the tritium-breeding blanket. If a liquid metal blanket is used, then an electrical insulator is typically required to prevent the magnetohydrodynamic (MHD) forces becoming prohibitive. This comes at the cost of increased complexity and manufacturing challenges. However, a feature of tandem mirror reactors is that the magnetic field is uniform and acts in the axial direction. This may therefore remove the need for the electrical insulator and enable a so-called single-coolant lead lithium (SCLL) blanket without the MHD forces being excessive. The primary objective of this project is therefore to determine whether MHD forces present, as with other fusion geometries, a significant barrier to utilization of an SCLL blanket in tandem mirrors. This will be achieved through applying the state-of-the-art 3D multiphysics modelling tools for fusion blankets under development at Oak Ridge National Laboratory, developed under DOE Office of Fusion Energy Sciences Funding (and therefore also providing an early stage, high impact use case). If SCLL blankets are enabled by this geometry, then this presents a rapid win for Realta Fusion and accelerates the path towards commercialization with simplified blanket technology. Alternatively, a more nuanced picture may emerge where careful design of the blanket inlet and outlet is required to limit MHD forces – in this case, then the research performed by ORNL will enable such design decisions to be made in follow on work.

Company PI: Dr. Craig Jacobson

Company e-mail: cjacobson@realtafusion.com

Institution: ORNL

Institution PI: Paul Humrickhouse, humrickhoupw@ornl.gov





INFUSE 2024, August 8, 2024

Company: Realta Fusion Inc., SAM UEI: MVSHELKP1GZ1

Title: Efficient Neutral Beam Injection for Mirror Fusion Reactors

Abstract:

Realta Fusion is an early-stage fusion company commercializing magnetic mirror fusion reactors. Realta Fusion aims to design and build the Break Even Axisymmetric Mirror (BEAM), a simple mirror which could serve as a fusion volumetric neutron source (FVNS). Following this, Realta intends to rapidly construct a tandem-mirror-based fusion pilot plant (FPP). Both concepts rely on 100 keV neutral beam injection (NBI) for plasma heating and fueling. In the FVNS, the injection energy is near the peak in the DT fusion reactivity such that the device operates near scientific breakeven. Development of an efficient steady state neutral beam is critical to Realta's mission, and the expertise of Lawrence Berkeley National Laboratory's (LBNL) Accelerator Technology and Applied Physics (ATAP) division is perfectly suited to address key issues in the neutralizer and ion dump regions of the NBI using particle-in-cell (PIC) simulations.

Company PI: Dr. Craig Jacobson

Company e-mail: cjacobson@realtafusion.com

Institution: LBNL

Institution PI: Arun Persaud, apersaud@lbl.gov





INFUSE 2024, August 8, 2024

Company: TAE Technologies, Inc, SAM UEI: J234C2JLE8W5

Title: Validation of Kinetic Models of FRC Stability against C-2W Experiment

Abstract:

On the road to commercializing fusion, privately-funded TAE Technologies has produced steady-state plasmas in field-reversed configurations suitable for advanced reactors. These have the highest possible plasma pressure with a modest applied magnetic field, opening the possibility for advanced fuel cycles. An essential feature of TAE's reactor design is the injection of energetic ions using neutral beams, a type of compact particle accelerator, to provide heating and drive plasma current by injecting energetic ions. The relative energy content of these "fast ions" exceeds that of other, more-studied plasma systems. This project will extend the understanding of the interaction of these fast ions with the background plasma. As a large part of the energy released by fusion is in the form of fast alpha particles, the understanding and control of fast particle physics is essential for a reactor to succeed. As is the case in tokamaks, TAE's plasmas exhibit bursts of oscillations associated with fast particles, and also show evidence that there is more than expected transfer of energy from the fast ions to the background plasma, which effect has been noted to be useful for improving reactor operation by increasing reactivity. In addition to the excellent and improving diagnostics of the experimental observations, it is essential to understand these physics theoretically, and some preliminary computational work has found modes with similar characteristics. In spite of this progress, agreement between theory and experiment is notably lacking. In particular, the computations show destructive modes which grow to uncontrollable size, while experimentally similar modes remain small and have benign or even beneficial effects. To resolve this dichotomy, TAE is teaming with Princeton Plasma Physics Laboratory (PPPL) to make use of their theory expertise and advanced, well-benchmarked computer codes to investigate several hypotheses as to the mitigating effects operating experimentally. In this joint project, PPPL will lead the computational study, while TAE will provide physics input from their experimental and related theoretical studies. The larger fusion community will benefit from the published conclusions by advancing the understanding of these essential fast-particle physics in conditions which extend those studied in the mainline public-funded programs.

Company PI: Dr. Sean Dettrick

Company e-mail: sean@tae.com

Institution: PPPL

Institution PI: Dr Elena Belova, ebelova@pppl.gov





INFUSE 2024, August 8, 2024

Company: Tokamak Energy, Inc., SAM UEI: N581GZDDDZE7

Title: Development of advanced, oxidation-resistant vanadium alloys for fusion blanket applications

Abstract:

Vanadium base alloys are leading candidate materials for breeder blanket structures in fusion reactor designs flowing liquid lithium because of their excellent lithium compatibility and superior hightemperature mechanical properties compared to reduced activation ferritic-martensitic steels and other structural materials. Blanket design activities at Tokamak Energy have indicated that a self-cooled liquid lithium blanket without an electrical insulator coating may not be viable due to the magnetohydrodynamic (MHD) pressure drop and the resulting parasitic load. A dual-cooled design with helium as the coolant obviates the need for an insulator coating and provides a more accessible design point. However, vanadium alloys have not been strongly considered for dual-cooled designs because of concerns with oxidation and embrittlement by the uptake of interstitial atoms including oxygen, carbon, nitrogen, or hydrogen. The most studied vanadium base fusion alloy, V-4Cr-4Ti, the prime candidate vanadium alloy previously selected by the U.S. Fusion materials program, has been shown to have unacceptable tensile elongation in oxygen bearing environments, including in high purity helium with < 0.1 vppm O2. Therefore, to enable development of a dual-cooled blanket design with liquid Li as the breeder, a vanadium base alloy with improved oxidation resistance and equivalent or better mechanical properties compared to V-4Cr-4Ti is required. The proposed work scope involves thermodynamic modelling to devise the optimal processing for V-Ti and V-Zr alloys containing between 7 and 15 wt.% Cr. Oxidation, thermomechanical property, and weld testing will be combined with microstructure characterization to evaluate the fabricated alloys. If this project is successful, the development of an advanced vanadium base alloy with improved oxidation resistance could potentially expand the use of these materials to more diverse environments, enable new design avenues, enhance safety under accident conditions, and improve plant efficiency.

Company PI: Dr. Aaron Washington

Company e-mail: aaron.washington@tokamakenergy.com

Institution: ORNL

Institution PI: Tim Graening, graeningt@ornl.gov





INFUSE 2024, August 8, 2024

Company: Type One Energy Group, SAM UEI: D26JC7VM3Q71

Title: High Temperature Superconducting Cable Testing and Optimization for Stellarator Fusion

Applications

Abstract:

To match the rising energy demand, it is imperative to explore sustainable and efficient energy solutions. Fusion power, specifically using stellarator configurations, presents a promising, scalable solution to this crisis. Stellarators, with their steady-state operation, offer a unique advantage in the field of fusion energy. However, their efficiency is contingent on the generation of high magnetic fields. High-Temperature Superconducting (HTS) cables, capable of both generating and withstanding high magnetic fields, play a pivotal role in ensuring the success of stellarator coils. In collaboration with the National High Magnetic Field Laboratory, Type One Energy aims to pioneer novel HTS cable topologies specifically designed for non-planar stellarator coils. The research involves short cable sample testing, mechanical property assessments, and detailed modeling of cable behavior. These investigations are essential for understanding the scalability and feasibility of these innovative designs. We believe the outcomes of this project could significantly advance the field of fusion energy and contribute to a sustainable future.

Company PI: Mr. Zachary Johnson

Company e-mail: zachary.johnson@typeoneenergy.com

Institution: Florida State University

Institution PI: Lance Cooley, Idcooley@asc.magnet.fsu.edu





INFUSE 2024, August 8, 2024

Company: Xcimer Energy Corporation, SAM UEI: KJLGRKMA6GG6

Title: Tritium extraction from flibe blankets using the CoRExt process

Abstract:

Xcimer Energy is developing the design of a fusion pilot plant for power production from inertial fusion energy. Xcimer's laser architecture, the key enabling technology, combines KrF excimer amplifiers and a novel pulse compression system to achieve high driver energies at low laser hardware cost. This driver advance allows for an attractive fusion plant design that uses an adaptation of the well-established and documented HYLIFE thick liquid-wall chamber concept to a commercial design. Xcimer has evaluated various options for its liquid wall and blanket systems and determined flibe to be the leading candidate for its fusion plant design. Flibe fusion blankets have significant benefits in terms of high breeding ratio and there is significant experience with molten salt systems in fission and clean energy technologies. Key challenges in developing flibe breeding blankets are defining how to mitigate corrosion that can be caused by TF produced during the breeding reactions and extraction of tritium from the fusion blanket. The Combined Redox Extraction (CoRExt) process proposed by the team at SRNL simultaneously performs redox control on flibe in a breeding blanket while extracting tritium. While the electrochemical reaction is driven by a galvanic electrochemical potential, there is the potential for only chemical reaction to occur at the active metal (e.g. Be electrode) in the system. If successful, this project will combine the unit operations for redox control and tritium extraction in flibe and increase their effectiveness. Both unit operations require high surface area contact of the salt with the walls and/or with a sweep gas. By combining these methods into a single system, it will reduce pressure drop while increasing the efficiency of both unit operations due to their proximity and shorter mass transfer differences.

Company PI: Dr. Susana Reyes

Company e-mail: sreyes@xcimer.net

Institution: SRNL

Institution PI: Luke Olson, luke.olson@srnl.doe.gov





INFUSE 2023, July 25, 2023

Company: Baker Hughes, DUNS / SAM UEI: 117834591

Title: Development of Tritium Sensors for Enabling Low-Carbon Technologies for FUSION (DETECT –

FUSION)

Abstract:

An important aspect to ensure the safety of nuclear fusion power plants is the prompt and accurate detection of any possible tritium leakages, which can pose serious health risks due to the ionizing radiation emitted during its decay. However, common detection methods such as a liquid scintillation counter or an ion chamber cannot be performed in real time, and more importantly, cannot pinpoint the exact location of a tritium leak. Compared to many traditional sensors, optical sensors have significant advantages due to their immunity to electromagnetic noise, flexible deployment, inexpensive nature, and opportunities for distributed sensing. This work aims to leverage these advantages to create a tritium area sensor that can be deployed to detect and pinpoint tritium leaks over large areas.

Company PI: Christopher Freeman

Company e-mail: christopher.freeman@bakerhughes.com

Institution: Penn State University

Institution PI: Federico Scurti, fus191@psu.edu





INFUSE 2023, July 25, 2023

Company: Bruker OST, DUNS / SAM UEI: 078601429000

Title: A low AC loss, fast ramp HTS solenoid prototype for compact Spherical Tokamak

Abstract:

The primary goal for this project is to build and test a Bi-2212 HTS insert prototype coil designed by Princeton Plasma Physics Laboratory (PPPL) for the next step compact spherical tokamak (ST) ohmic heating central solenoid in a fusion pilot plant (FPP). The central core of a ST pilot plant is its innovative in-board coil system. For a ST pilot plant, its largest superconducting magnet challenge is the center column where the combined in-board toroidal field (TF) and Ohmic Heating (OH) coils are assembled inside a center stack casing where plasma facing components are attached. A high field, high temperature superconductor (HTS) solenoid coil inside the bore of TF inner leg bundle will decouple the inner TF bundle from the central solenoid to avoid trapping the OH coil outside the inner TF bundle lead flags. Recent evaluations of Bi-2212 wires have shown that Bi-2212 conductors have two orders of magnitude lower AC losses compared to any REBCO conductors, very comparable to ITER Nb3Sn wires. This makes Bi-2212 wires suitable and potentially the only viable high field option for a fast ramp of high field solenoid for compact ST operations. This is significant because most recent studies in support of private fusion companies have shown promising results of net fusion gain by operating a pulsed tokamak machine.

Company PI: Yibing Huang

Company e-mail: yibing.huang@bruker.com

Institution: PPPL

Institution PI: Dr. Yuhu Zhai, yzhai@pppl.gov





INFUSE 2023, July 25, 2023

Company: Commonwealth Fusion Systems, DUNS / SAM UEI: 117005109

Title: Electrochemical Evaluation of Hydrogen Concentration and Diffusivity in FLiBe

Abstract:

Tritium breeding, confinement and extraction technologies are required to ensure the technical viability of deuterium-tritium based fusion energy. They also have important implications for radiological source terms, worker safety, public safety, and public acceptance of fusion energy. CFS will employ FLiBe (i.e. molten Li2BeF4) as the liquid breeding material for ARC. Concentration and diffusivity of tritium in FLiBe are the two dominant properties that govern the tritium transport characteristics within the blanket and associated systems, and transport properties flow down to design and performance of tritium systems. However, tritium concentration and diffusivity depend on electrochemistry, and impurities from salt manufacturing, environmental contamination, and corrosion products. These dependencies are not well understood.

Currently, published data describing diffusivity and concentration of the two dominant tritium species expected to exist within a FLiBe blanket (3H2 & 3HF) is limited and inconsistent. This proposal will produce an electrochemical test method to determine solubility and diffusivity of hydrogenic species in FLiBe.

Company PI: Caroline Sorensen

Company e-mail: csorensen@cfs.energy

Institution: UC Berkeley

Institution PI: Raluca Scarlat, scarlat@berkeley.edu





INFUSE 2023, July 25, 2023

Company: Commonwealth Fusion Systems, DUNS / SAM UEI: 117005109

Title: Deuterium retention in boron dust

Abstract:

Reliable, high-performance operation of present-day tokamaks relies on proper conditioning of the plasma facing components. A common method, known as boronization,

involves the application of thin boron coatings to in-vessel surfaces. These boron films improve plasma performance. However, boron has been found in present-day devices and laboratory experiments to retain non-negligible amounts of hydrogen isotopes. This is of significant concern since it projects to high tritium retention estimates. Tritium retention in-vessel is a concern for two reasons: (1) it prevents manned access of the device for maintenance; (2) it limits the amount of tritium in circulation as part of the fuel cycle and reduces the amount available for injection during plasma pulses. In addition, boron dust is not easily removed, and will continue to accumulate over the operational lifetime. No data exists on boron dust tritium retention. This proposal studies deuterium retention in boron dust, using deuterium as a surrogate for experimental simplification, and describing the operational and safety profile of boronization as a tool for fusion power plants.

Company PI: Adam Kuang

Company e-mail: akuang@cfs.energy

Institution: PPPL

Institution PI: Alessandro Bortolon, abortolo@pppl.gov





INFUSE 2023, July 25, 2023

Company: Commonwealth Fusion Systems, DUNS / SAM UEI: 117005109

Title: Informing ARC divertor design and plasma facing material selection through integrated modeling

Abstract:

The ARC commercial power plant will require successful plasma facing material (PFM) candidates able to survive extreme operational environments. PFCs will have to satisfy several distinct requirements simultaneously, including having low tritium retention, low sputtering or erosion, high thermal conductivity after neutron irradiation, high mechanical strength to resist cracking after neutron irradiation and in the presence of a high internal thermal stress, and maintain a continuous bond to the substrate structural material. It is currently unknown which of these issues will be the lifetime determining factors. This proposal evaluates a novel alloy for PFC use an integrated modeling code suite.

Company PI: Lauren Garrison

Company e-mail: lgarrison@cfs.energy

Institution: UCLA

Institution PI: Jaime Marian, jmarian@g.ucla.edu





INFUSE 2023, July 25, 2023

Company: Focused Energy Inc., DUNS / SAM UEI: 118411704

Title: Design of proton diagnostics operating at high repetition rate to advance proton fast ignition

Abstract:

Focused Energy is pursuing a laser-driven inertial fusion energy (IFE) scheme for commercial fusion based on proton fast ignition (PFI). PFI is an advanced fusion energy scheme that separates the fuel compression and ignition stages, offering the potential to reach the high target gains needed for IFE in a robustly performing platform. Ignition is initiated by a high-intensity, picosecond-scale, laser-generated beam of energetic protons that deposits its energy into the compressed deuterium-tritium (DT) fuel, driving a thermonuclear burn wave. The ability to optimize the proton ignitor beam for PFI relies on diagnostics that can operate at enhanced shot rates and withstand the harsh radiation environment of a fusion reactor chamber. This project will leverage Princeton Plasma Physics Lab's (PPPL) extensive experience in developing and testing proton diagnostics to design state-of-the-art diagnostics that meet the requirements of PFI. PPPL will provide detailed designs of the diagnostic suite needed to optimize the proton ignitor beam, based on an extensive review of the existing technological solutions, as well as on the use of numerical tools allowing validation of the detector performance.

Company PI: Andrea Hannasch

Company e-mail: andrea.hannasch@focused-energy.world

Institution: PPPL

Institution PI: William Fox, wfox@pppl.gov





INFUSE 2023, July 25, 2023

Company: Gauss Fusion Inc., DUNS / SAM UEI: 118972072

Title: Opportunities for Fusion Coil System in a Compact Spherical Tokamak using Low Cost, High Field

Superconductors Made in USA

Abstract:

This project will explore the use of Nb3Sn RRP® superconductors in a compact spherical tokamak (ST) for opportunities for toroidal field (TF) and central solenoid (CS) coils by leveraging the experience, knowledge and modeling capabilities of the Princeton Plasma Physics Laboratory (PPPL). Also, as a head-to-head comparison between low temperature superconductor (LTS) and high temperature superconductor (HTS) technologies this project will evaluate Bi-2212 round conductors. Finally, because the poloidal field (PF) coils are relatively low field (5T-7T), this project will also evaluate the very low cost NbTi conductors (used in MRI machines and manufactured in volumes of hundreds of thousands of kilometers per year). By studying all three conductor types this project expects to recommend an optimum coil system for a compact ST fusion power plant.

Company PI: Lawrence Masur

Company e-mail: larry.masur@gauss-fusion.com

Institution: PPPL

Institution PI: Yuhu Zhai, yzhai@pppl.gov





INFUSE 2023, July 25, 2023

Company: HB11 Energy USA LLC, DUNS / SAM UEI: 118972177

Title: Design and simulation of innovative p-11B targets for IFE

Abstract:

HB11 Energy is pursuing a laser-driven inertial fusion energy (IFE) power plant to realize large-scale electricity generation from the fusion of hydrogen with boron-11. If proton-boron fusion can be realized, there are many engineering benefits over traditional deuterium-tritium (DT) fusion that will result in the production of a dramatically simpler and safer reactor. However, proton-born fusion reactions require higher temperatures than DT, so the challenge is to identify how big the lasers need to be to burn this fuel. The goal of this INFUSE project is to partner with the University of Rochester Laboratory for Laser Energetics to use their state-of-the-art tools to simulate the proton fast ignition of proton-boron fuels and determine what laser power and energies are required for practical energy production. The resulting target designs will also guide HB11's target fabrication efforts. Further, detailed information on the lasers and targets will improve the accuracy of power plant design and costing models.

Company PI: Thomas Mehlhorn

Company e-mail: thomas.mehlhorn@hb11.energy

Institution: Univ. Rochester

Institution PI: Adam B Sefkow, asef@lle.rochester.edu





INFUSE 2023, July 25, 2023

Company: Helion Energy, DUNS / SAM UEI: 079379584

Title: Nonlinear kinetic simulation study of non-equilibrium and merging FRCs

Abstract:

Numerical study of field reversed configuration (FRC) acceleration, merging and non-equilibrium stability will be performed using the 3D nonlinear hybrid code (HYM), developed at PPPL. Helion Energy Inc. fusion concept is based on FRC acceleration, merging and compression to achieve a high temperature plasma. Helion's 6th Prototype, Trenta, was comprised of two magnetically driven accelerators, each of which produced and accelerated an FRC to high velocity while simultaneously compressing it. During the FRCs merging, the kinetic energy is converted to ion thermal energy, while the magnetic compression further increases the plasma temperature. Hybrid version of the HYM code includes the fluid electrons and fullorbit kinetic (Particle-In-Cell) description of the thermal ions. In the simulations, the FRC parameters and profiles will be varied to understand their effects on FRC stability during the acceleration phase and the merging process and estimate the possible stability limits. Three-dimensional and 2D kinetic simulations of FRC merging will be compared with the corresponding MHD results to understand the effects of kinetic ions on FRC merging and investigate stability properties of FRCs with fast changing plasma parameters. 3D hybrid simulations of FRC acceleration will also be performed to study the FRC stability properties during the acceleration/translation phase and investigate how the stability time scales depend on the plasma parameters within and outside the experimental range. The simulation results will be used to identify the corresponding signatures in the experimental diagnostics and compared against the actual experimental measurements. Improved understanding the physics of the FRC merging, its dependence on the plasma parameters, and scaling with the device size is important for achieving the goals of the Helion experimental program and planning of the next-step fusion prototype. The scientific contributions from the Department of Energy funded research will accelerate progress toward the development of fusion energy in the private sector.

Company PI: Anthony Pancotti

Company e-mail: pancotti@helionenergy.com

Institution: PPPL

Institution PI: Elena Belova, ebelova@pppl.gov





INFUSE 2023, July 25, 2023

Company: Kyoto Fusioneering America Ltd., DUNS / SAM UEI: 118966752

Title: A Multiphysics Simulation of Magnetohydrodynamic Li-Pb Flow in a Blanket Module with SiCf/SiC

as Structural Material

Abstract:

The development of advanced liquid metal magnetohydrodynamics (LMMHD) simulation tools is crucial for progress in fusion energy research. Current codes, however, often lack user-friendly interfaces and portability for broader applications. This project aims to adapt an established multiphysics computational framework like ANSYS (finite-element analysis system) to facilitate the development of liquid metal (LM) blankets, which could accelerate the evaluation of design concepts and experimental mockups. By leveraging ANSYS's state-of-the-art numerical methods, this approach has the potential to enable more efficient and accurate LM blanket development. Recent work at the Princeton Plasma Physics Laboratory (PPPL) has demonstrated promising advancements, particularly for high Hartmann numbers. This collaborative effort between PPPL and KFA (Kyoto Fusioneering America) seeks to extend the applicability of the multiphysics formulation to commercially viable blanket designs and accelerate the development of its own self-cooled lithium lead blanket.

Company PI: Bibake Uppal

Company e-mail: b.uppal@kyotofusioneering.com

Institution: PPPL

Institution PI: Andrei Khodak, akhodak@pppl.gov





INFUSE 2023, July 25, 2023

Company: Kyoto Fusioneering America Ltd., DUNS / SAM UEI: 118966752

Title: Evaluating Lithium-Lead Mixtures for Increased Tritium Breeding in Fusion Energy Blanket Systems: Exploring the Impact of Composition and Temperature

Abstract:

This project investigates hypereutectic liquid lithium-lead (Li-Pb) as a coolant in fusion blanket systems, with a focus on testing the compatibility of compositions with better tritium breeding ratios (TBR). The 12-month study concentrates on static corrosion experiments, comparing silicon carbide (SiC) corrosion rates in Li-rich and eutectic Li-Pb mixtures, and also examining interactions between Mo and Li-Pb. The research seeks to determine the maximum operating temperatures for this material combination, acknowledging the balance between Li-Pb melting temperature and achievable TBR to unlock new opportunities for blanket design. This work lays the groundwork for future collaboration between Kyoto Fusioneering and Oak Ridge National Laboratory. Findings could enhance the TBR of fusion blanket designs, and impact fusion energy development by confirming material compatibility between different compositions of Li-Pb with SiC and Mo at higher temperatures, including at temperatures relevant for very high-temperature blankets (1000°C), which could enable higher electricity conversion efficiencies and commercial applications using process heat.

Company PI: Chris Dorn

Company e-mail: c.dorn@kyotofusioneering.com

Institution: ORNL

Institution PI: Bruce Pint, pintba@ornl.gov





INFUSE 2023, July 25, 2023

Company: Kyoto Fusioneering America Ltd., DUNS / SAM UEI: 118966752

Title: Evaluating Lithium Compatibility for Electrode Materials Used in an Electrolysis-Based Tritium

Extraction Process

Abstract:

The project aims to advance liquid lithium (liq-Li) technology as a fusion blanket coolant and tritium breeding material for fusion energy production, offering excellent thermal properties and high tritium-breeding efficiency. A major challenge in using liq-Li is the efficient extraction of tritium. This research will focus on the Direct LiT Electrolysis process, employing lithium lanthanum zirconate (LLZO) solid electrolyte, to extract tritium from liq-Li. The project's objectives include characterizing electrolyte mechanical properties, determining electrode and process properties for integration into the UNITY loop, and exploring impurity removal in Li coolant. UNITY stands for UNique Integrated Testing FacilitY, which is currently under development by Kyoto Fusioneering to research and test key fusion fuel cycle and power cycle technologies. Success in developing and demonstrating this technology will make liq-Li a more attractive option for the fusion industry, promoting innovation in blanket designs, and contributing to the development of a successful fusion power plant.

Company PI: Chris Dorn

Company e-mail: c.dorn@kyotofusioneering.com

Institution: SRNL

Institution PI: Christopher Dandeneau, christopher.dandeneau@srnl.doe.gov





INFUSE 2023, July 25, 2023

Company: Princeton Stellarators, Inc., DUNS / SAM UEI: 118736608

Title: Developing a renewable first wall with boron pebbles.

Abstract:

As stellarator reactors are steady state, heat removal and tritium recovery will be challenging without a rapidly renewable first wall. This INFUSE proposal aims to develop a boron based renewable first wall that is capable of sufficient heat removal and tritium recovery from stellarator fusion devices. A technique to make boron pebble rods will be developed. The pebble rods will then be bench-tested under plasma environment as well as reactor relevant heat loads.

Company PI: Santhosh Kumar

Company e-mail: santhosh.kumar@princetonstellarators.energy

Institution: UCSD

Institution PI: Eric Hollmann, ehollmann@ucsd.edu





INFUSE 2023, July 25, 2023

Company: Realta Fusion, DUNS / SAM UEI: MVSHELKP1GZ1

Title: ORNL Portable Diagnostic Package for Evaluating Mirror Performance

Abstract:

The Oak Ridge National Lab Portable Diagnostics Package is being used to evaluate capabilities of a new class of magnetic mirror fusion reactor. The diagnostic is deployed on the Wisconsin High-temperature-superconducting Axisymmetric Mirror (WHAM1.0, built at the University of Wisconsin-Madison), which is a prototype for the endcell of mirror-based fusion reactor. Evaluation of the scaling of the electron temperature in WHAM1.0 is a mission-critical task, which informs estimates of the cost and performance of both the power producing mirror and the nearer-term fusion volumetric neutron source.

Company PI: Kieran Furlong

Company e-mail: kieran@realtafusion.com

Institution: ORNL

Institution PI: Theodore Biewer, biewertm@ornl.gov





INFUSE 2023, July 25, 2023

Company: Stellarex, Inc., DUNS / SAM UEI: 118817947 / RRSZSJJC4977

Title Efficient Tritium Extraction from Liquid Lithium

Abstract:

This INFUSE project focuses on experimentally testing and measuring the operating performance of an electrochemical method of separating tritium from liquid metals in tritium breeding blankets. The target fusion application for this work is SX1, a stellarator fusion energy plant planned by Stellarex Inc. This technology should also be applicable to other types of fusion systems. Stellarex is partnering with the Savannah River National Laboratory (SRNL), who will measure the key operating properties of the separation process and examine several potential ways to improve the process. The results will be used in a techno-economic analysis of the best configuration of the separator in a fusion blanket system.

Company PI: Michael Zarnstorff

Company e-mail: michael.zarnstorff@stellarex.energy

Institution: SRNL

Institution PI: Christopher Dandeneau, christopher.dandeneau@srnl.doe.gov





INFUSE 2023, July 25, 2023

Company: TAE Technologies, DUNS / SAM UEI: 065262557

Title: Integrated kinetic modeling of a biased expander using Aleph code

Abstract:

Neutral beam injection, electrode biasing, and expander tank are TAE critical systems designed to generate hotter, denser, and more stable plasma with greater reproducibility. Specifically, the expander tank and the electrode biasing perform several key roles, among them: (1) decouple hot electrons from the wall to reduce electron heat losses; (2) applied voltage (bias) at end electrodes propagates to the middle of the machine to setup a radial electric field and stabilize the Field-Reversed Configuration (FRC) plasma against rotational modes. These enhancements depend on the electrostatic potential generated in the expander divertor as well as the propagation of the electrode applied bias along the magnetic flux lines. Both can be dramatically modified and diminished by the presence of neutrals, plasma-material interactions such as secondary electron emission, or the presence of molecular gas. In this RFA we propose to collaborate with Sandia National Lab to leverage the DOE developed code Aleph to conduct an integrated modeling of the expander tank and the biased electrodes in the presence of plasma, neutrals, plasma material interaction and secondary electron emission processes. In particularly we will concentrate on modeling (1) the relationship between the plasma jet into the expander and resultant current on the electrodes, and (2) the relationship of the return bias current on neutral and plasma condition in front of the electrodes. Furthermore, we will use the results to design a diagnostic electron beam for probing the pre-sheath and sheath structure.

Company PI: Ales Necas

Company e-mail: anecas@tae.com

Institution: SNL

Institution PI: Zakari Eckert, zeckert@sandia.gov





INFUSE 2023, July 25, 2023

Company: TAE Technologies, DUNS / SAM UEI: 065262557

Title: In-situ measurements of hydrogen-titanium plasma-material interactions for model validation

Abstract:

IGNIS, a facility for in-situ measurement of plasma-material interactions at the University of Illinois at Urbana-Champaign (UIUC), will be used to measure the interaction of hydrogen plasmas with titanium samples. TAE's C2-W uses titanium gettering to reduce impurities and control hydrogen recycling from vessel walls and plasma facing components such as limiters and divertor plates.. Titanium offers a safe and effective wall conditioning for TAE's Advanced FRCs, but titanium as a plasma-facing material has been understudied since the widespread adoption of high-Z materials such as tungsten and low-Z coatings such as boron or lithium in the fusion community. TAE's next-step machine, Copernicus, will use similar wall conditioning to C2-W, but in plasma conditions beyond those observed in C2-W. TAE has developed a numerical model of hydrogen-titanium interactions that includes implantation, reflection, and sputtering simulated using a free and open-source Binary Collision Approximation code, RustBCA, coupled to an in-house model of hydrogen diffusion and outgassing that is being used to understand the physics of the plasma-material interface in C2-W and make predictions of plasma-material interactions (PMI) for the conditions expected in Copernicus. However, validation of the model using C2-W results is challenging, due to the inability to separate the plasma-material interface from the larger plasma physics of the machine; there is a crucial need to validate the model decoupled from the plasma physics to increase confidence in integrated models including PMI and predictions for Copernicus, and for application to other materials. The IGNIS facility at UIUC was purpose-built for experiments complementary to fusion PMI and offers a suite of sources and diagnostics appropriate for model validation. In this partnership, scientific contributions from the University of Illinois will both advance confidence in a free and open-source code that is of wide interest to the fusion community and improve TAE's modeling of the specific plasmamaterial interface in our devices, advancing our ability to understand and predict PMI in future fusion machines. Additionally, this type of model, consisting of a BCA coupled to a diffusion model, may be broadly useful in the modeling of other fusion-relevant materials, such as boron.

Company PI: Jon Drobny

Company e-mail: jdrobny@tae.com

Institution: UIUC

Institution PI: R Mohan Sankaran, rmohan@illinois.edu





INFUSE 2023, July 25, 2023

Company: Tokamak Energy Inc, DUNS / SAM UEI: N581GZDDDZE7

Title: Post irradiation examination of nickel doped fusion steels irradiated in the High Flux Isotope

Reactor (HFIR)

Abstract:

Tokamak Energy is planning to run a pilot fusion plant (ST-E1) in the early 2030s which will be imposing severe neutron damage on the reduced activation ferritic/martensitic (RAFM) steels that will be the main structural materials. The damage modes of particular concern are the atomic displacements leading to vacancy and self-interstitial defect generation (typically quantified in displacements per atom (dpa)), the transmutation reactions generating gaseous products such as helium (typically quantified in atomic parts per million (appm)), and most critically the combination of the two, which will significantly impact hardening, embrittlement and swelling behavior in ways that are hard to predict. There have been various attempts to simulate the combined effect (e.g. using spallation proton neutron irradiations, or multi-ion beam irradiations), but the most promising approach is to expose Ni-doped steels to fission neutrons in a Materials Test Reactor. Doping with 58Ni enhances helium production to the levels observed in the fusion environment, while 60Ni control samples can be used to deconvolute the alloying effects of the Ni.

The Oak Ridge National Laboratory (ORNL) High Flux Isotope Reactor (HFIR) has conducted many long (> 10 year) irradiation campaigns of fusion-relevant materials but the funding has not allowed Post Irradiation Examination (PIE) of some samples of particular interest to Tokamak Energy and the broader fusion community, including Ni-doped RAFM steels irradiated to 40-60 dpa. This is the level of damage predicted after 9 calendar years of operation in the TE pilot plant (with its expected availability of 20%). Samples were irradiated at both 300 degreesC and 500 degreesC, and, when combined with baseline RAFM steel samples irradiated at 300 degreesC, they are a highly valuable resource for illuminating the likely performance of the ST-E1 structural materials over the early years of operation.

It is proposed that these samples be tested at the ORNL Irradiated Materials Examination and Testing (IMET) facility and the Low Activation Materials Development and Analysis (LAMDA) facility. Investigations will include microindentation hardness, fracture toughness (using the Master Curve method), and microstructural characterization (with transmission electron microscopy) to investigate cavity size distribution and density (ii) dislocation line density (iii) dislocation loop size distribution and density (iv) solute clustering or precipitation (v) grain boundary segregation and cavitation. The cavity size distribution will be used to calculate volumetric swelling, while the results on the dislocations and solute clusters/precipitates will be used to inform hardening and embrittlement models. In addition, grain boundaries will be assessed for features that may contribute to intergranular failure. Atom probe tomography (APT) will also be used outside of ORNL to quantify the size and number density of any nanoscale clusters or precipitates formed under irradiation. In particular, data on any Ni-enriched clusters/precipitates are required to deconvolute any dopant alloying effects.





The specific information that this project should produce on samples with combined displacement damage and helium transmutation is: low temperature (300 degreesC) information on hardening and embrittlement (providing an intermediate data point between existing data on F82H (a representative RAFM steel) at ~18 dpa and ~68 dpa (displacements per atom), and high temperature (500 degreesC) information on swelling, extending the existing 8.6 dpa data on F82H up to 45-50 dpa (equivalent to 2 years of full power operation in planned reactors). These latter data will determine whether the swelling will exceed the 5% swelling generally considered unacceptable for structural applications.

These data will be invaluable for informing design and determining structural material lifetimes under fusion neutron exposure for TE and all of the other fusion pilot plant development programs supporting the US decadal vision for accelerating fusion energy.

Company PI: Mark Koepke

Company e-mail: mark.koepke@tokamakenergy.com

Institution: ORNL

Institution PI: Tim Seibert, graeningt@ornl.gov





INFUSE 2022b, January 17, 2023

[VACATED]

Company: Commonwealth Fusion Systems, DUNS: 117005109

Title: A modern neutronics-modeling uncertainty methodology towards a future fusion neutronics

handbook

Abstract:

This program proposes to take the first step towards developing a handbook-grade documentation of fusion neutronics workflows for the fusion powerplant era. We propose to update the SINBAD database with modern tools and datasets, simulate the SINBAD experiment with those tools, gather the data necessary to perform a comprehensive uncertainty analysis of that simulation output, and, apply these modern workflows and uncertainty analyses to a prototypical ARC neutronics simulation. This work will benefit both CFS and the broader fusion community by providing a modernized neutronics modeling guide that includes a comprehensive uncertainty treatment.

Company PI: Ms. Corinne Mitchell

Company e-mail: cmitchell@cfs.energy

Institution: ORNL

Institution PI: Michael Loughlin, loughlinmj@ornl.gov





INFUSE 2022b, January 17, 2023

Company: Commonwealth Fusion Systems, DUNS: 117005109

Title: Oxide Dispersion Strengthened Ferritic Steel Wire Feedstock Development for Large-Format

Additive Manufacturing

Abstract:

This INFUSE project seeks to demonstrate the viability of fabricating large, complex-parts from oxide dispersion strengthened (ODS) steel with advanced manufacturing. Exhibiting excellent radiation tolerance and high mechanical performance at elevated temperatures, ODS steel is a promising structural material candidate for near-plasma components in fusion energy systems. Its use, however, has been limited by a lack of manufacturability. This project will seek to produce ODS steel wire through a solid-state shear assisted extrusion process and then demonstrate that the wire can undergo controlled local melting while being welded with the final part sufficiently retaining the beneficial properties of ODS steel. This would allow the use of wire-arc additive manufacturing (WAAM) to manufacture large-scale ODS parts, even though ODS is currently only available as a powder. WAAM is a promising technique for producing components like the replaceable ARC vacuum vessel.

Company PI: Dr. Cody Dennett

Company e-mail: cdennett@cfs.energy

Institution: PNNL

Institution PI: Dalong Zhang, dalong.zhang@pnnl.gov





INFUSE 2022b, January 17, 2023

Company: Energy Driven Technologies LLC, DUNS: 080060913

Title Retention of Fusion Plasma Species in PFC Candidate Fine-Grain Dispersion-Strengthened Tungsten Materials

Abstract:

This project is a collaboration between Energy Driven Technologies and Sandia National Laboratories in Livermore, CA. This work will expose PFM candidate fine-grain dispersion-strengthened tungsten to high fluence, low energy deuterium, and helium plasmas to evaluate retention behavior and resilience of the microstructure and surface morphology compared to ITER-grade tungsten.

Company PI: Mr. Zachariah Koyn

Company e-mail: zkoyn@editekk.com

Institution: SNL

Institution PI: Jonathan Coburn, jdcobur@sandia.gov





INFUSE 2022b, January 17, 2023

Company: Focused Energy Inc., DUNS: 118411704

Title: Simulation study for risk assessment of laser-plasma instabilities in proton fast ignition

Abstract:

Focused Energy is pursuing a laser-driven inertial fusion energy (IFE) scheme for commercial fusion based on proton fast ignition (PFI), an advanced inertial confinement fusion scheme. Proton fast ignition has the potential to reach the high target gains needed for IFE in a robustly performing platform. A key scientific risk in laser driven fusion is the potential for laser-plasma instabilities (LPI), which can reduce energy coupling efficiency and drive uniformity.

In this INFUSE project Focused Energy will partner with Los Alamos National Laboratory (LANL) to apply state-of-the-art simulation tools developed at LANL, and high-performance computing resources, to evaluate the LPI physics risks for fast ignition target designs and assess mitigation techniques.

Company PI: Dr. Pravesh Patel

Company e-mail: pravesh.patel@focused-energy.world

Institution: LANL

Institution PI: Dr. Brian Albright, balbright@lanl.gov





INFUSE 2022b, January 17, 2023

Company: Focused Energy Inc., DUNS: 118411704

Title: Model validation of low-density foams wetted with liquid deuterium and tritium for inertial fusion

target optimization

Abstract:

In the proton fast ignitor inertial fusion scheme, the assembly of a high-density inertial fusion target and the subsequent heating of a small "ignition spark" region are separated. The former being driven by a spherically distributed configuration of nanosecond-scale laser beams while the latter derives from a highintensity, picosecond-scale laser which accelerates protons that subsequently deposit their energy into the ignition spark region temporally near peak compression. With the compression and heating phases separated, the symmetry and thermodynamic requirements associated with producing an isobaric central hot spot are eliminated, allowing for more robust and higher gain designs. Traditional inertial fusion targets are created using a multi-day manufacturing process called beta-layering which relies on the slow nuclear decay of tritium into \$^3\$He. In order to create an inertial fusion power plant on par with existing electrical power plants, a new target manufacturing process must be used that can scale with the necessary shot rate of an inertial fusion reactor. One such manufacturing process uses low-density foams wetted with deuterium and tritium. This process greatly reduces manufacturing times and minimizes fabrication oversight. For this process to become viable, high-resolution, three-dimensional model validation must be done using state-of-the-art radiation-hydrodynamics codes to characterize the compressive behavior of this heterogeneous material, which could then be used in the computational design of inertial fusion reactor targets.

Company PI: Dr. Leonard Jarrott

Company e-mail: charlie.jarrott@focused-energy.world

Institution: LLNL

Institution PI: Dr. Elijah Kemp, kemp10@llnl.gov





INFUSE 2022b, January 17, 2023

Company: General Atomics, DUNS: 067638957

Title: Machine learning-accelerated predictions of power and particle exhaust in a fusion pilot plant

Abstract:

This project will utilize LLNL expertise in the development of machine learning-based surrogate models for predicting plasma detachment in a fusion pilot plant (FPP) under conceptual design at General Atomics. Built upon a latent space representation, the surrogate models will be used to identify promising regimes for handling the extreme heat and particle loads that will occur in the FPP. The results will be used to guide higher fidelity physics and engineering design activities.

Company PI: Dr. Jonathan Yu

Company e-mail: yujh@fusion.gat.com

Institution: LLNL

Institution PI: Ben Zhu, zhu12@llnl.gov





INFUSE 2022b, January 17, 2023

Company: Princeton Stellarators Inc, DUNS: 118736608

Title: Determining fast particle behavior in a reactor-relevant Quasi-Axisymmetric stellarator equilibrium

Abstract:

Princeton Stellarators, Inc. (PSI) will collaborate with Princeton Plasma Physics Laboratory (PPPL) to analyze fast particle behavior in candidate stellarator equilibria. Particles of very high energy are introduced into fusion reactors in several ways, notably as the product of fusion reactions and injected via Neutral Beam Injectors. Historically, the stellarator concept of plasma confinement has had difficulty confining these fast particles. Recently, stellarator equilibria have been developed that so precisely exhibit a property known as quasi-symmetry that they are expected to confine the large majority of fast particles. PSI has identified such an equilibrium as the starting point of its reactor design. In this project, PPPL will analyze the behavior of fast particles in this equilibrium and subsequent versions. This will allow PSI to develop better equilibria, and allow PSI's reactor design to proceed to a much higher fidelity in several important ways.

Company PI: Dr. Charles Swanson

Company e-mail: charles.swanson@princetonstellarators.energy

Institution: PPPL

Institution PI: Phillip Bonofiglo, pbonofig@pppl.gov





INFUSE 2022b, January 17, 2023

Company: Princeton Stellarators Inc, DUNS: 118736608

Title: Stellarator evolution modelling

Abstract:

We are proposing to work with PPPL to use new tools, which is expected to be available in early 2023, to understand the effect of bootstrap current on island growth in stellarator geometry. The tools are modifications to the PPPL flagship code M3D-C1 which is a time dependent resistive MHD code. The two planned changes are to add a "Sauter-like" model (valid only in quasi-symmetric configurations) and also interface to the SFINCS code by Landreman (U. Maryland) to M3D-C1. these tools will be benchmarked against each other and used to understand neoclassical island healing in stellarator-like magnetic shear.

Company PI: Dr. Mike Martin

Company e-mail: mike.martin@princetonstellarators.energy

Institution: PPPL

Institution PI: Adelle Wright, awright@pppl.gov





INFUSE 2022b, January 17, 2023

Company: Tokamak Energy Inc, DUNS: 117135313

Title: Evaluation of the effect of coolant purity on the corrosion resistance of Castable Nanostructured

Alloys for structural application in tokamak reactor blankets

Abstract:

TE will use Castable Nanostructured Alloy (CNA) steels in future reactors because of their higher operation temperature and superior neutron resistance compared with current generation reduced activation ferritic-martensitic (RAFM) steels but needs to understand the likely lifetime of such materials under operating conditions, particularly as a result of their chemical compatibility with potential coolants, such as lithium, and to understand how the coolant purity might impact that lifetime.

Stage 1: Static testing -- In year 1, a series of capsule tests using a range of temperatures and C, O and N impurities will be evaluated. The capsule experiments will yield (1) mass change, (2) effects on room temperature tensile properties and (3) changes in microstructure or surface composition as revealed by specimen characterization including metallographic cross-sections and electron microscopy including energy dispersive spectroscopy to measure composition profiles.

Stage 2: Flowing testing -- In year 2, a thermal convection loop (TCL) will be built from CNA and operated twice for 500-1000 h. The baseline would operate with a peak temperature of 600 C and use a Li composition selected from Stage 1. The selection of experimental conditions (flow and temperature) will be guided by the blanket design study that is being conducted by Tokamak Energy. If this project is successful, it will address one of the main concerns regarding such blanket concepts by either determining whether corrosion is a concern, or at least delineating safe operating conditions in terms of temperature and coolant purity.

Tokamak Energy intends to employ a Li-based blanket to breed tritium and extract heat and has an aggressive deployment strategy. In order to meet that timeline, it is essential that basic materials science issues, such as Li compatibility with structural materials, are quickly addressed so that more complex aspects, like the effect of irradiation can then be investigated. While RAFM steels like CNAs are expected to have reasonably good compatibility with Li, no data currently exist and the results suggest that Li purity standards are needed. Furthermore, the data was not generated in a thermal gradient where mass transfer can occur. Previous research in flowing Li in a thermal gradient was last conducted in the 1980s.

Company PI: Naomi Mburu

Company e-mail: naomi.mburu@tokamakenergy.com

Institution: ORNL

Institution PI: Bruce Pint, pintba@ornl.gov





INFUSE 2022b, January 17, 2023

Company: Type One Energy Group Inc., DUNS: 117343133

Title: High-temperature superconducting CORC® conductors for stellarator magnet applications

Abstract:

BCMT and TOE will collaborate through the INFUSE program, sponsored by DOE Office of Fusion Energy Sciences, to validate the technical feasibility of HTS conductors, especially the CORC® conductors, making and testing small bend radius coils for 3D non-planar high field stellarator magnet designs.

Company PI: Mr. Paul Harris

Company e-mail: pharris@typeoneenergy.com

Institution: LBNL

Institution PI: Xiaorong Wang, xrwang@lbl.gov





INFUSE 2022a, June 15, 2022

Company: Commonwealth Fusion Systems, DUNS: 117005109

Title: Characterization of Turbulent Transport and Confinement in ARC with STEP and CGYRO

Abstract:

This project is a collaboration between CFS and the University of California, San Diego (UCSD) to develop a more detailed characterization of microturbulence dynamics expected in a future ARC power plant and determine the extent to which these same dynamics will be observed in SPARC. The work will entail three main activities:

- 1. Translating 0D empirical predictions of ARC design points into first-principles 1.5D transport solutions using the OMFIT STEP workflow.
- 2. Benchmarking TGLF and CGYRO predictions of core turbulent transport in ARC.
- 3. Comparing expected ARC and SPARC turbulence characteristics.

Company PI: Dr. Alex Creely

Company e-mail: alex@cfs.energy

Institution: UCSD

Institution PI: Dr. Chris Holland, chholland@ucsd.edu





INFUSE 2022a, June 15, 2022

Company: Commonwealth Fusion Systems, DUNS: 117005109

Title: Assessing ELM mitigation by pellet triggering in SPARC low-collisionality discharges

Abstract:

The main deliverable of this project is to answer the question if pellet ELM triggering is feasible in SPARC, which scenarios are likely/unlikely to allow pellet ELM triggering, and which poloidal injection location is the most promising in SPARC.

Company PI: Dr. Chris Chroback

Company e-mail: cchrobak@cfs.energy

Institution: ORNL

Institution PI: Dr. Andreas Wingen, wingen@fusion.gat.com





INFUSE 2022a, June 15, 2022

Company: Commonwealth Fusion Systems, DUNS: 117005109

Title: Machine learning assisted prediction of tungsten heavy alloy plasma facing component

performance for fusion energy applications

Abstract:

This project aims to leverage existing deep learning models expertise and tools developed at MIT to study thermal and mechanical material properties in high heat flux environments and apply them to the application of tungsten heavy alloy plasma-facing components in the SPARC tokamak. The key deliverable will be a tool to predict remaining component lifetime.

Company PI: Dr. Dina Yuryev

Company e-mail: dyuryev@cfs.energy

Institution: MIT

Institution PI: Dr. Markus Buehler, mbuehler@mit.edu





INFUSE 2022a, June 15, 2022

Company: Commonwealth Fusion Systems, DUNS: 117005109

Title: Agile design workflow for plasma-facing fusion components with coupled thermofluidic and

structural optimization

Abstract:

This project will build a design optimization workflow for plasma-facing components in fusion devices that couples thermofluid and structural analysis, and incorporates the constraints and requirements of advanced manufacturing. The workflow builds on an existing one designed for the Transformational Challenge Reactor program at ORNL.

Company PI: Dr. Caroline Sorensen

Company e-mail: caroline@cfs.energy, line@mit.edu

Institution: ORNL

Institution PI: Dr. Justin Weinmeister, weinmeistejr@ornl.gov





INFUSE 2022a, June 15, 2022

Company: General Atomics, DUNS: 067638957

Title: Fuel Cycle and Tritium Plant Model for Fusion Pilot Plant

Abstract:

General Atomics (GA) is developing a modeling workflow for fusion pilot plant (FPP) integrated design and optimization and is in need of verified and validated models for the tritium fuel cycle. Savannah River National Laboratory (SRNL) will develop two models for GA's use: a reduced model for tritium processing which will be integrated into GA's proprietary FPP systems code, as well as comprehensive Aspen fuel cycle simulations to assess the significance of particular design decisions. GA and SRNL will perform FPP optimizations with these tools and SRNL will provide a relative, initial cost analysis for the tritium processing facilities.

Company PI: Dr. David Weisberg

Company e-mail: weisbergd@fusion.gat.com

Institution: SRNL

Institution PI: Dr. Holly Flynn, Holly.Flynn@srnl.doe.gov





INFUSE 2022a, June 15, 2022

Company: General Fusion Corp., DUNS: 117111477

Title: Tritium Fuel Cycle Modelling and Optimization to Enable Fusion Pilot Plant Development

Abstract:

General Fusion will partner with Savannah River National Laboratory (SRNL) to model the total inventory of tritium in General Fusion's future Commercial Pilot Plant (CPP) -- the first General Fusion machine that will use tritium as a fuel. Understanding tritium inventory is a necessary step to design, license, construct, and operate larger and increasingly integrated fusion machines. SRNL, the leading DOE laboratory for tritium process research, development, and demonstration, will apply its expertise to quantify and streamline tritium processing in the CPP to enable fusion pilot plant development to deliver clean, safe, and on-demand fusion power at industrial scale.

Company PI: Dr. Ryan Guerrero

Company e-mail: ryan.guerrero@generalfusion.com

Institution: SRNL

Institution PI: Dr. George Larsen, George.Larsen@srnl.doe.gov





INFUSE 2022a, June 15, 2022

Company: General Fusion Corp., DUNS: 117111477

Title: Beyond Neoclassical Closures for MHD Simulation of General Fusion Devices via Kinetic Monte

Carlo Calculations

Abstract:

General Fusion and Oak Ridge National Laboratory will cooperatively enhance open plasma modelling tools to enable large scale calculations of kinetic electron orbits in fusion plasmas. These tools will enable a powerful approach to efficient modelling of General Fusion's Magnetized Target Fusion (MTF) devices. This modelling will enable high fidelity study of General Fusion's Fusion Demonstration Plant, a first-of-a-kind MTF demonstration facility that the company is building at the Culham Centre for Fusion Energy and will accelerate the design and construction of a commercial fusion plant to deliver clean, safe, and ondemand fusion power at industrial scale.

Company PI: Dr. Colin McNally

Company e-mail: colin.mcnally@generalfusion.com

Institution: ORNL

Institution PI: Dr. Mark Berrill, berrillma@ornl.gov





INFUSE 2022a, June 15, 2022

Company: HelicitySpace, DUNS: 117087016

Title: Observing Density Evolution During Merging of Plectonemic Taylor states

Abstract:

The project requests the assistance of Swarthmore College's expertise to build a set of diagnostics to measure plasma density at several locations simultaneously in the company's new fusion proof-of-concept experiment called ECLAIR. The new fusion concept relies on the merging of plectonemic Taylor states first observed at Swarthmore on the SSX experiment and later on the MOCHI experiment at the University of Washington. The diagnostic will be tested on SSX first before shipping them and implementing them on ECLAIR. The results will be compared to existing theory and numerical simulations to help determine the viability of the new fusion concept.

Company PI: Dr. Setthivoine You

Company e-mail: setthivoine.you@helicityspace.com

Institution: Swarthmore University

Institution PI: Dr. Mike Brown, mbrown3@swarthmore.edu





INFUSE 2022a, June 15, 2022

Company: Magneto-Inertial Fusion Technologies, Inc. (MIFTI), DUNS: 078640171

Title: 3D modeling of the Staged Z-pinch with the FLASH code

Abstract:

The Staged Z-pinch (SZP) fusion concept is a magneto-inertial compression scheme in which small amounts of fusion fuel are brought to fusion-relevant conditions by passing multi-million amperes strong current through a cylindrical shell of high atomic number material. One- and two-dimensional modeling with the MACH2 code suggests that net fusion energy gain can be achieved when currents in the 10 million amperes range compress a 50%-50% mixture of deuterium and tritium gas. In this project we will use the FLASH code to execute high-fidelity, three-dimensional simulations of various SZP configurations, in collaboration with the Flash Center for Computational Science at the University of Rochester and the Laboratory for Laser Energetics. FLASH is a high-performance computing, multi-physics, radiation-magnetohydrodynamic (MHD) code with extended physics capabilities, which is developed at the Flash Center. The goal of this project is to assess the shell/fuel stability of the pinch to three-dimensional MHD instabilities and to utilize FLASH's extended physics capabilities to understand how extended-MHD effects impact implosion dynamics and plasma conditions at stagnation. The project is a natural extension of our ongoing collaboration with the Flash Center through the ARPA-E BETHE program and will provide us with simulation capabilities that are currently beyond our reach with MACH2. Ultimately, we want FLASH to become one of our simulation workhorses for reliable, high-fidelity SZP platform design.

Company PI: Dr. Emil Ruskov

Company e-mail: emil@miftec.com

Institution: Univ. Rochester

Institution PI: Dr. Petros Tzeferacos, p.tzeferacos@rochester.edu





INFUSE 2022a, June 15, 2022

Company: Magneto-Inertial Fusion Technologies, Inc. (MIFTI), DUNS: 078640171

Title: Hard x-ray imaging and characterization of staged z-pinch plasmas in order to exclude ion beams

as cause of fusion

Abstract:

When deuterium and tritium nuclei collide with enough energy to overcome their mutual repulsion they can fuse and release many times more energy than was invested. While this fusion process offers bountiful energy production, it is extremely challenging because of the difficulty in confining the reacting nuclei long enough to obtain a return on the energy that was invested. Confined nuclei develop random thermal motion, so this energy-producing process is called thermonuclear fusion. The Staged Z Pinch is a promising fusion concept that has already indicated significant fusion yields as evidenced by substantial neutron production. However, there is a possibility that these neutrons were produced by local particle beam instabilities rather than from well-confined nuclei. It is thus important to determine whether the neutrons are thermonuclear in origin or from beam instabilities as the former process leads to scalable energy production while the latter does not. The presence or lack thereof of spurious fusion from particle beam instabilities will be established by measuring the X-rays produced at the Magneto-Inertial Fusion Technologies Inc. (MIFTI) Staged Z-pinch experiment in operation at the University of California San Diego. This will be done by a Caltech team that has developed a 128-channel X-ray detector that has been designed to image X-ray instabilities and additionally measure X-ray energies. These measurements are capable of distinguishing X-rays produced by beam-target instabilities from X-rays produced by thermonuclear processes as the former are more localized, more directed, and more energetic than the latter. The X-ray diagnostic now operates in a linear one-dimensional mode with 128 channels and will be upgraded to have 256 channels arranged in a 16x16 pixel array so at to provide a two-dimensional imaging capability. The scintillator material will be upgraded to enable faster (8 nanosecond) time resolution than the existing time resolution (20 nanoseconds). The system will resolve X-ray energies as low as 4 keV and as high as 80 keV, where energies in the range of 4-10 keV indicate thermonuclear fusion whereas energies above 20 keV indicate beam-target fusion. This partnership between MIFTI and Caltech will provide a significant step forward in developing the staged Z pinch as a viable fusion energy concept.

Company PI: Dr. Hafiz Rahman

Company e-mail: hafiz@miftec.com

Institution: CalTech

Institution PI: Dr. Paul Bellan, pbellan@caltech.edu





INFUSE 2022a, June 15, 2022

Company: Princeton Fusion Systems, Inc., DUNS: 805686870

Title: Electron density profiles on PFRC with USPR

Abstract:

UC Davis has, under prior ARPA-E funding, updated their diagnostic and prepared hardware to attach it to the PFRC-2 experiment at PPPL; however, in no small part due to COVID, funds will now only allow the diagnostic to visit the HIT-SIU device in Seattle, WA.

INFUSE funds will cover the cost of transporting the ARPA-E USPR system to Princeton, NJ, to install and commission the system on the PFRC device, and to operate the system and collect/analyze time-resolved density profile data.

Company PI: Dr. Chris Galea

Company e-mail: cgalea@psatellite.com

Institution: UC-Davis

Institution PI: Dr. Neville C. Luhmann, Jr., cwdomier@ucdavis.edu





INFUSE 2022a, June 15, 2022

Company: Princeton Fusion Systems, LLC, DUNS: 805686870

Title: Evaluating RF antenna designs for PFRC plasma heating and sustainment

Abstract:

We will perform numerical modeling of new antenna concepts and designs that improve power coupling to the plasma ions, allow easier installation and maintenance, provide greater flexibility in containment-vessel and axial-magnet-array design, and expand the power range of PFRC-type fusion reactors. This project will inform design decisions for next-generation devices as well as for power-producing reactors.

Company PI: Mr. Michael Paluszek

Company e-mail: map@psatellite.com

Institution: PPPL

Institution PI: Dr. Samuel Cohen, scohen@pppl.gov





INFUSE 2022a, June 15, 2022

Company: Princeton Fusion Systems, LLC, DUNS: 805686870

Title: Stabilizing PFRC plasmas against macroscopic low-frequency modes

Abstract:

Numerous approaches have been implemented in or proposed for FRC devices to slow the rate-of-growth of and stabilize these modes. Examples of successful experimental methods are: loffe bars, biased rings, energetic beam injection, gas puffing, and RF fields. Gas-dynamic-trap conditions and other flow and flow-shear methods may also provide stability. With this INFUSE assistance we will perform numerical studies to benchmark the TriForce code against the existing PFRC-2 experiment and analyze any discovered instabilities. We will then simulate several stabilizing mechanisms, such as gas puffing and loop biasing.

Company PI: Ms. Stephanie Thomas

Company e-mail: sjthomas@psatellite.com

Institution: PPPL

Institution PI: Dr. Samuel Cohen, scohen@pppl.gov





INFUSE 2022a, June 15, 2022

Company: SuperPower, Inc. DUNS: 832548338

Title: Performance-structure characterization to improve REBCO Fusion conductor production at

SuperPower

Abstract:

The central goal of this project is to generate testing and characterization data that support SuperPower's coated conductors that will be used by the fusion industry. SuperPower anticipates difficulty meeting upcoming specifications with high yield without changes to present production methods. This work aims to understand root causes responsible for property variations. Since capability to measure the performance at 20 T and 20 K exist only in national user facilities in Japan and at the NHMFL in the USA, there is insufficient routine testing to understand the critical properties of the product that is coming off the production line. This work taps into the extensive characterization database at NHMFL and augments it with new measurements to provide rapid feedback to new conductors being made at SuperPower with properties of highest relevance to the fusion industry. Micro- and nano-structural analyses will also be made at NHMFL to connect structure-property relationships and refer them to processing. Prior long collaborations between the two PIs are formally extended to immediate challenges of fusion by this project.

Company PI: Dr. Yifei Zhang

Company e-mail: yzhang@superpower-inc.com

Institution: FSU

Institution PI: Dr. Dmytro Abraimov, abraimov@asc.magnet.fsu.edu





INFUSE 2022a, June 15, 2022

Company: TAE Technologies, Inc, DUNS: 065262557

Title: Development of a High-Flux Inductive Spheromak Gun for FRC Formation via Counter-Helicity

Merging

Abstract:

We ultimately aim to combine TAE's high-power NBI technology with PPPL's well-studied and fully developed spheromak-merging FRC formation technique. TAE and PPPL have already begun a collaboration under the INFUSE program (2020b award) whose objective is to investigate the feasibility of high-magnetic-flux FRC formation via counter-helicity spheromak merging for C-2W. In this ongoing collaboration, we have constructed a relatively small spheromak injector that fits well to the MRX device at PPPL to demonstrate the proof-of-principle and a preliminary experiment has already commenced. Meanwhile, in this new INFUSE project, in order to scale-up the spheromak injector to C-2W-relevant level and achieve a high-magnetic-flux FRC (up to ~30 mWb), we aim to develop a new spheromak gun that enables a novel high-flux spheromak formation scheme via inductive flux injection at a size still compatible to C-2W. Initial high-flux spheromak formation and merging experiments with the upgraded gun will be conducted on MRX, after which the spheromak guns can eventually be installed in C-2W to produce a high-magnetic-flux FRC via spheromak merging. It would allow more effective capture of injected fast NBI particles, thus enhancing the effect of NB heating and current drive to achieve C-2W FRC plasmas of higher energy density in the future.

Company PI: Dr. Hiroshi Gota

Company e-mail: hgota@tae.com

Institution: PPPL

Institution PI: Dr Masaaki Yamada, myamada@pppl.gov





INFUSE 2022a, June 15, 2022

Company: TAE Technologies, Inc, DUNS: 065262557

Title: THz Radiation Generation to Enable Internal Magnetic Field Measurement of Burning Plasmas

Abstract:

Over the last 20 years, TAE Technologies (TAE) has developed an advanced beam-driven Field-Reversed Configuration (FRC) for superior plasma confinement limited by power supply and not by physics. In collaboration with Google, TAE has developed an equilibrium reconstruction tool to better understand plasma stability, transport and confinement; however, the tool is only as good as the supplied data. TAE utilizes a state-of-the-art plasma diagnostic to measure internal density, electron and ion temperature with the magnetic field measured outside the plasma only. The reconstructed equilibria are well validated with simulation; however, the internal magnetic field heavily relies on models since a direct measurement in missing. TAE has embarked on the first-ever direct and non-perturbative measurement of the internal magnetic field topology of an FRC. To that end we are developing a pulsed polarimetry diagnostic. Pulsed polarimetry is a Lidar technique that combines two well-known diagnostic techniques of Thomson scattering and polarimetry to provide profiles of $n_e(s)$, $T_e(s)$ and $B_{\parallel}(s)$ along the laser sightline. The rate of change of Faraday angle with distance, $\Delta\alpha/\Delta s$, is directly proportional to the local $[n_eB_{II}(s)]$ product. To achieve a large progressive Faraday rotation and maintain Thompson scattering incoherent, a pulse of THz light (<100 ps) is required; however, there are no commercially available THz sources powerful (>1 mJ) enough. Such powerful sources are under laboratory and simulation investigation in a process whereas relativistic laser irradiates a target achieving 1% efficiency and 10's mJ THz pulse. TAE has partnered with the Laboratory for Laser Energetics at the University of Rochester to develop a THz source for the pulsed polarimetry. In this public-private partnership, scientific contributions from the Department of Energy will directly accelerate progress toward the development of fusion energy in the private sector and beyond as we believe the pulsed polarimetry can be applied to any magnetized fusion device. Pulsed polarimetry improves with density and machine size, and thus is compatible with burning plasmas.

Company PI: Dr. Ales Necas

Company e-mail: anecas@tae.com

Institution: Univ. Rochester

Institution PI: Dr Gerrit Bruhaug, gbru@lle.rochester.edu





INFUSE 2022a, June 15, 2022

Company: Tokamak Energy, Inc., DUNS: 117135313

Title: FLARED -- Flowing Lithium's Adsorption and Release Experiment for Deuterium

Abstract:

The Center for Plasma Material Interactions (CPMI) at U. Illinois at Urbana Champaign is the premier academic lithium technology lab in the U.S. Other molten metals have been studied as well. CPMI is a strong proponent of the low-recycling divertor concept which utilizes a flowing-liquid-lithium divertor plate. The low-recycling concept achieves higher confinement times, higher core-electron temperatures and a more stable plasma. Existing work with TE, described in a recent paper showing that the low-recycling concept can lead to a much more affordable fusion-energy device [De Castro, Moynihan, Stemmley, Szott, and Ruzic, "Lithium, a path to make fusion energy affordable", Phys. Plasmas 28 (2021) 050901], seeks to create a reactor-compatible flowing-lithium-divertor plate for testing in ST40. Specifically, the existing contract calls for the creation of a lithium loop and testing of all loop components and for high-heat-flux testing of the divertor plate using an electron beam, whereas, this proposal asks if the hydrogen can be extracted from the lithium in a complete and timely manner [Allain, Nieto, Coventry, Neumann, Vargas-Lopes, Ruzic, "FLIRE—Flowing Liquid Surface Retention Experiment, Design and Testing" Fusion Engineering and Design 61-62 (2002)245-250].

Adding a plasma source to the lithium loop and testing the distillation column will help address the most serious objection to the low-recycling paradigm. There are several concepts for liquid lithium divertors / first walls in overcoming challenges of using liquid metals in this way: Capillary Pore System (CPS); slow-flowing thin films (FLiLi); medium-speed self-flowing thermoelectric MHD (TEMHD) driven flows; and fast flowing lithium. As previously mentioned, TE has been directly sponsoring work with CPMI for 3 years to develop a reactor-compatible TEMHD self-flowing liquid-lithium-divertor that can be tested in the ST40 spherical tokamak.

Liquid lithium's ability to pump (adsorb and retain) deuterium and tritium has pros and cons. The advantage arises because alternate methods of deuterium and tritium pumping during a transient plasma (and continuously in a reactor) are more technically challenging and because present best-practices, e.g., cryo-pumps, do not scale to continuous operation. The disadvantage arises because the retention of tritium in liquid lithium depends on (1) how quickly liquid lithium pumps tritium, and (2) how quickly the tritium can be separated from the liquid lithium and neither of these adsorption and extraction properties are understood theoretically and technologically, at this time. Quantifying both properties is the purpose of this project having the long-range goal of enabling an advance towards the use of liquid lithium in a reactor design. Previous experiments using deuterium plasma have measured the pumping rate with stationary liquid lithium. However, deuterium is only absorbed in a thin layer of the liquid lithium surface which quickly becomes saturated. Therefore, we expect the pumping rate of flowing liquid to be higher, where the surface is constantly being replenished. The significance of the project is the anticipated





fundamental measurement of lithium's ability to pump deuterium while flowing which, perhaps surprisingly, has yet to be made. Our methodology is designed to overcome the technical challenges of working with large quantities of liquid lithium, perhaps the constraint in other labs that now can be overcome at UIUC CPMI. In the past, CPMI constructed a complete flowing liquid lithium loop and measured the pumping of hydrogen gas in the FLIRE experiment. However, we expect the pumping rate of (ionized) plasma to be different to that of neutral gas. The CPMI team is presently constructing a new and improved liquid lithium loop under the TEMHD-ST40 project that TE is already sponsoring. We plan to use this new loop within this INFUSE project.

Deuterium absorbs into lithium by dissolving, known as 'alpha-phase', and by chemically reacting to form lithium hydride, known as 'beta-phase'. Separating the alpha-phase is comparatively simpler and involves heating the liquid lithium and exposing a free surface to vacuum, whereas separating the beta-phase requires thermal decomposition. CPMI has developed and tested a distillation column which was supplied with lithium hydride and has shown it does perform the more challenging task of separating the beta-phase. During experiments, the liquid lithium will be contained within the lab, away from water, and will not be under pressure. When the experiment is not running, the lithium will be frozen.

To our knowledge, CPMI is the only institution that has tested a distillation column. We will incorporate a plasma source into a closed-loop liquid lithium system, test the distillation column, and quantify the distillation-column efficiency for a representative distribution of alpha and beta phases. CPMI has an excellent safety record of working with liquid lithium. We emphasize that the fundamental measurements and results from this project will be applicable to any flowing liquid-lithium concept, and that this project is aligned to both TE's and CPMI's long-term goals.

Company PI: Dr. Mark Koepke

Company e-mail: Mark.Koepke@tokamakenergy.com

Institution: UIUC

Institution PI: Dr. David Ruzic, druzic@illinois.edu





INFUSE 2022a, June 15, 2022

Company: VWG, Inc. dba Xcimer Energy, DUNS: 118546777

Title: Simulation of Direct-Drive Hybrid Using Two Opposed Beams for Inertial Fusion Energy

Abstract:

Xcimer Energy plans to construct a novel facility to deliver high-energy laser light at low cost, with many of the characteristics needed for inertial fusion energy (IFE). Details of this architecture naturally support a target that is illuminated by two opposed beams. Several preliminary designs have been developed to exploit this space, including a novel Direct-Drive Hybrid target design, termed the DDH, which seeks to benefit from recent advances in the field. Physics-based modeling would inform Xcimer of the tradeoffs in this approach, identify risks and options for improvement, and lead to an integrated system with reduced cost and complexity. This program would leverage the unique tools and expertise available at the University of Rochester's (UR's) Laboratory for Laser Energetics (LLE). The codes LILAC and DRACO have been developed and validated against an extensive set of experimental data, and include the necessary aspects of laser absorption, x-ray production, and hydrodynamics. Xcimer Energy and LLE will work to implement a version of the hybrid design in both codes, and LLE will evaluate aspects of the DDH in 1-D and 2-D. Outputs will reduce uncertainty with respect to hybrid drive, the techniques used to obtain good implosion symmetry with two-sided illumination, and the potential for high gain. Findings could apply broadly to many types of drivers, increase the parameter space available to IFE, and motivate more extensive partnerships in the broader community.

Company PI: Dr. Conner Galloway

Company e-mail: cgalloway@xcimer.net

Institution: Univ. Rochester

Institution PI: Dr. Cliff Thomas, ctho@lle.rochester.edu





INFUSE 2021b, November 22, 2021

Company: Commonwealth Fusion Systems, DUNS: 117005109

Title: Magnetic Pumps for Molten Salt Fusion Devices

Abstract:

Commonwealth Fusion Systems (CFS) plans to complete construction of ARC, an affordable compact fusion power plant in the early 2030's. ARC will employ a novel liquid immersion blanket design that uses a molten lithium salt as both the tritium breeding material and the vacuum vessel coolant. FLiBe is currently the leading salt candidate due to its favorable heat transfer, neutronic, and tritium breeding properties. ARC will also require a FLiBe-compatible molten salt pump that can handle high temperatures and high pumping powers.

This program leverages Oak Ridge National Laboratory's (ORNL's) expertise in high-temperature, canned-rotor magnetic bearing pumps. This category of pump is well suited for service in ARC because it does not expose any internal seals or bearings to the molten salt. The ORNL and CFS team will identify modifications needed to adapt an existing ORNL salt pump design to meet ARC's requirements. The team will also experimentally test and evaluate the dielectric strength of insulation materials needed to reach ARC's power requirements. If successful, the program will accelerate CFS' molten salt pump roadmap for ARC.

Co. PI: Dr. Brandon Sorbom

Co. e-mail: brandon@cfs.energy

Laboratory: ORNL

Lab PI: Dr Alex Melin, melina@ornl.gov





INFUSE 2021b, November 22, 2021

Company: Commonwealth Fusion Systems, DUNS: 117005109

Title: Neutron Ion Handshake for Fusion Materials

Abstract:

Commonwealth Fusion Systems plans to complete construction of ARC, an affordable compact fusion power plant in the early 2030's. ARC's vacuum vessel needs to withstand high temperatures, mechanical loadings, and intense neutron radiation fields. A testing program is required to enable the judicious selection of structural materials that can withstand radiation-induced degradation. However, such programs have been hampered by the lack of appropriate neutron sources, long program timelines and high costs.

This program leverages the unique *in situ* ion irradiation transient grating spectroscopy facility at Sandia National Laboratories and its state-of-the-art shared materials analytical facilities to establish an equivalency between ion irradiation and neutron irradiation testing of candidate materials. If successful, the program will simplify and accelerate ARC materials testing, enabling testing of fusion-relevant materials at speeds three orders of magnitude faster than is possible with neutron irradiation test reactors.

Co. PI: Dr. Brandon Sorbom

Co. e-mail: brandon@cfs.energy

Laboratory: SNL

Lab PI: Dr. Khalid Hattar, khattar@sandia.gov





INFUSE 2021b, November 22, 2021

Company: Energy Driven Technologies LLC., DUNS: 080060913

Title: High Heat Flux Exposure of PFC Candidate Fine-Grain Dispersion-Strengthened Tungsten Materials

Abstract:

Energy Driven Technologies (a.k.a. Editekk) is developing a plasma facing material for future burning-plasma magnetic thermonuclear fusion reactors. While tungsten is an attractive option due to its high melting temperature, good thermal conductivity, and high sputtering threshold, current monolithic tungsten suffers from brittleness and grain growth under heavy thermal loads. Editekk' s approach is to use advanced manufacturing to create fine-grain dispersion-strengthened tungsten to improve thermomechanical properties. To achieve this goal and offer a material solution, this project will subject candidate samples to prototypical high heat fluxes using an electron beam facility. These tests will demonstrate material performance under extreme thermal loading and check for damage, such as melting and crack formation, as well as microstructural changes, such as grain growth. Results of these tests will guide development of the manufacturing process and demonstrate feasibility of Editekk's material design approach.

Co. PI: Mr. Zachariah Koyn

Co. e-mail: zkoyn@editekk.com

Laboratory: ORNL

Lab PI: Dr. Travis Gray, graytk@ornl.gov





INFUSE 2021b, November 22, 2021

Company: Energy Driven Technologies LLC., DUNS: 080060913

Title: Mechanical Characterization of PFC Candidate Fine-Grain Dispersion-Strengthened Tungsten

Materials

Abstract:

Energy Driven Technologies (a.k.a. Editekk) is developing a plasma facing material for future burning-plasma magnetic thermonuclear fusion reactors. While tungsten is an attractive option due to its high melting temperature, good thermal conductivity, and high sputtering threshold. Current monolithic tungsten suffers from brittleness and grain growth under heavy thermal loads. Editekk's approach is to use advanced manufacturing to create fine-grain dispersion-strengthened tungsten to improve thermo-mechanical properties. To achieve this goal and offer a material solution, this project will test the high temperature mechanical properties of candidate materials including tensile strength, ductile-to-brittle transition temperature, flexural strength, thermal diffusivity, the ability to inhibit grain growth after prolonged exposure to high temperatures and how this exposure affects properties, such as hardness. Results of these tests will define mechanical properties, guide the development of the manufacturing process, and demonstrate feasibility of Editekk's material design approach.

Co. PI: Mr. Zachariah Koyn

Co. e-mail: zkoyn@editekk.com

Laboratory: ORNL

Lab PI: Dr. Lauren Garrison, garrisonlm@ornl.gov





INFUSE 2021b, November 22, 2021

Company: General Atomics, DUNS: 067638957

Title: In-Field Performance Testing of a Novel HTS CICC for Practical and Cost-Effective Fusion Magnet

Systems

Abstract:

High temperature superconducting (HTS) magnets could significantly enhance the performance of fusion devices and are recognized as one of the four first-tier transformative enabling capabilities to efficiently advance fusion technology. General Atomics (GA) is actively evaluating the technical feasibility of largescale HTS fusion magnets. One of the focus areas at GA is the demonstration of an HTS-based segmented toroidal field (STF) coil at a scale typical of a compact tokamak fusion device. GA's design of the STF coil uses a unique configuration of Conductor-on-Round-Core (CORC®) HTS cables in a Cable-In-Conduit-Conductor (CICC). The CICC concept is novel approach to have an internally cooled conductor with large current capacity. The use of CORC® compared to the stacked and/or twisted tape cables enable a round geometry and isotropic properties which are favorable attributes in terms of fabrication as well as tokamak operation. Thus, the CORC-based CICC design offers a simplified and cost-effective solution to large-scale HTS magnets. Under this project, GA is fabricating a 4 m long test article of the CORC®-based CICC that will be tested under high-applied currents and high magnetic field conditions at the DCC017 dipole system at Brookhaven National Laboratory. The parametric evaluation of the test article that includes the tight radius bend will retire key manufacturing risks by demonstrating the integrity of CORC[®] cable inside the copper stabilizer and welded SS conduit. If successful, the project will demonstrate the technical feasibility of full-scale HTS fusion magnets and provide a path towards compact high-density plasma fusion machines.

Co. PI: Dr. Zbigniew Piec

Co. e-mail: Zbigniew.piec@ga.com

Laboratory: BNL

Lab PI: Dr. Ramesh Gupta, gupta@bnl.gov





INFUSE 2021b, November 22, 2021

Company: Magneto-Inertial Fusion Technologies, Inc. (MIFTI), DUNS: 078640171

Title: Thermonuclear fusion verification of Staged Z-pinch fusion on a 0.5 MA LTD pulsed power

generator

Abstract:

Magneto-Inertial Fusion Technologies, Inc. (MIFTI) is developing a fusion concept based on the oldest fusion idea, the Z-pinch, and refines it by surrounding the fusion fuel with a high atomic number cylindrical plasma shell. This so-called Staged Z-Pinch concept was recently successfully tested on the one million ampere pulsed power generator Zebra where krypton plasma shell compressed a deuterium target producing ten billion thermonuclear neutrons. MIFTI is about to start experiments on a five hundred thousand ampere pulsed power generator utilizing Linear Transformer Driver (LTD) technology which has more efficient energy coupling to the plasma load. We propose to use neutron diagnostics developed by the Lawrence Livermore National Laboratory to accurately measure the neutron yield on this machine. Monte-Carlo code simulations will clarify the neutron scattering properties of the LTD device and facility and will inform the interpretation of the neutron time of flight measurements along multiple sightlines, which are essential for establishing the thermonuclear neutron origin.

Co. PI: Dr. Emil Ruskov

Co. e-mail: emil@miftec.com

Laboratory: LLNL

Lab PI: Dr. Drew Higginson, higginson2@llnl.gov





INFUSE 2021b, November 22, 2021

Company: Renaissance Americas Inc., DUNS: 117506666

Title: Artificially intelligent optimization of alpha particle transport in stellarators

Abstract:

Stellarator optimization requires rapid evaluation of physical properties associated with the magnetic equilibrium. However, certain optimization targets such as alpha losses are computationally costly to evaluate. With experts in machine learning from the Princeton Plasma Physics Laboratory (PPPL) we will:

- 1) generate an open-source dataset of burning stellarator equilibria,
- 2) efficiently evaluate alpha losses from such equilibria, and
- 3) generate machine-learned proxies for those metrics.

These proxies will aid Renaissance and the whole stellarator community in designing future reactors.

Co. PI: Dr. Christopher Berg Smiet

Co. e-mail: chris.smiet@renfusion.eu

Laboratory: PPPL

Lab PI: Dr R. Michael Churchill, rchurchi@pppl.gov





INFUSE 2021b, November 22, 2021

Company: Silver-Fir Software, Inc, DUNS: 117147222

Title: Extension of MCNP® Mesh Based Weight Windows to Support Unstructured Mesh Topologies

Abstract:

In this project, the capabilities of the MCNP Monte Carlo code will be extended by Los Alamos National Laboratory to support weight windows defined on unstructured mesh topologies. As a cost-share contribution, Silver Fir Software will extend the capabilities of Attila4MC to support the new MCNP unstructured mesh weight window format.

Co. PI: Dr. Eugeny Sosnovsky

Co. e-mail: gene.sosnovsky@silverfirsoftware.com

Laboratory: LANL

Lab PI: Dr. Joel A. Kulesza, jkulesza@lanl.gov





INFUSE 2021a, June 14, 2021

Company: Commonwealth Fusion Systems, DUNS: 117005109

Title: Informing Layout and Performance Requirements for SPARC Massive Gas Injection

Abstract:

Commonwealth Fusion Systems (CFS) is designing a compact tokamak called SPARC and is evaluating massive gas injection (MGI) as its primary means of plasma disruption mitigation technique. Present conservative scoping has enabled a preliminary design of the MGI system. However, physics-based modeling can help CFS inform an optimized layout, which can either reduce the cost of MGI system by reducing the number of gas injectors or provide supporting evidence that present scoping estimates are correct.

This program leverages the 3D magneto-hydrodynamic modeling expertise at Princeton Plasma Physics Laboratory (PPPL), which is maintained through the development and use of the M3D-C1 code. CFS and PPPL will develop a gas source model representative of SPARC MGI's system. PPPL would then use M3D-C1 to simulate unmitigated SPARC disruptions, to develop a baseline response, and then simulate mitigated disruptions representing a variety of MGI system configurations. The specific output of this program will reduce risks associated with disruptions on SPARC, make SPARC's disruption mitigation system more cost-effective, a benefit that will carry to commercial fusion devices. The methodology developed by this program is expected to have wide benefits, independent of the design details, and have potential applications to other future power-producing fusion device concepts.

Co. PI: Dr. Matthew Reinke

Co. e-mail: mreinke@cfs.energy

Laboratory: PPPL

Lab PI: Dr Nathaniel Ferraro, nferraro@pppl.gov





INFUSE 2021a, June 14, 2021

Company: Commonwealth Fusion Systems, DUNS: 117005109

Title: Active Redox Control of Molten Salts for Fusion Blankets

Abstract:

Commonwealth Fusion Systems is investigating FLiBe molten salt as a novel blanket material for its fusion tokamak. However, FLiBe is known to cause significant degradation to structural materials via impurity-driven corrosion. The use of FLiBe for commercial fusion applications will require the application of corrosion mitigation strategies, including monitoring impurities and salt chemistry, controlling impurity levels, and ensuring protection of salt-facing structural materials.

This program leverages the expertise in electrochemical and corrosion engineering at Savannah River National Laboratory to monitor corrosion caused by FLiBe in real time, and to enable local control of corrosion rates by adjusting impurity concentrations in the FLiBe. Electrochemical reference electrodes will be used to detect the presence of hydrogen isotopes and of corrosion products. An active redox control system that maintains stable redox conditions in response to real-time sensor output will be demonstrated.

Co. PI: Dr. Brandon Sorbom

Co. e-mail: brandon@cfs.energy

Laboratory: SRNL

Lab PI: Dr. Brenda Garcia-Diaz, Brenda.Garcia-Diaz@srnl.doe.gov





INFUSE 2021a, June 14, 2021

Company: General Atomics, DUNS: 067638957

Title: Performance Testing of Low-Resistance Demountable HTS Joints for Large Segmented Magnets

Abstract:

High temperature superconducting (HTS) magnets could significantly enhance the performance characteristics of fusion devices and are recognized as one of the four first-tier transformative enabling capabilities to efficiently advance fusion technology. General Atomics (GA) is actively evaluating the technical feasibility of large-scale HTS fusion magnets. One of the focus areas at GA is the demonstration of an HTS-based segmented toroidal field (TF) coil at a scale representative of a compact tokamak fusion device. Practical configurations of magnet coils for future fusion devices, such as TF coils, will require demountable, high current, low-resistance joints. A method for reliably constructing such joints is essential for the application of HTS to fusion magnet systems, as the ability to remove a quadrant of the TF coils permits access to the machine's internals and simpler exchange of components. The goal of the present project is to significantly advance the current state-of-the-art HTS conductor and joint technology beyond tabletop experimentation. Under this project, GA will design and fabricate test articles of the HTS joints and perform basic testing for superconductivity at a temperature of 77 Kelvin. The detailed testing at a temperature of 4.5 Kelvin will be conducted at Lawrence Berkeley National Laboratory's (LBNL) unique facilities ideally suited to the testing of superconducting joints under high magnetic fields and high transport currents. LBNL also has expertise in the instrumentation of such test samples, which is crucial to ensure the viability of the results. The project will provide important joint performance data for the development and demonstration of the HTS demountable joint technology that is novel, generic, scalable, and parallelizable, thus promising dramatic simplification and cost reduction for any fusion concept benefiting from demountable HTS coils. The program will demonstrate the technical feasibility of demountable HTS magnets and provide a path towards compact high-density plasma fusion machines.

Co. PI: Dr. Zbigniew Piec

Co. e-mail: Zbigniew.piec@ga.com

Laboratory: LBNL

Lab PI: Dr. Xiaorong Wang, xrwang@lbl.gov





INFUSE 2021a, June 14, 2021

Company: HelicitySpace., DUNS: 117087016

Title: Simulation of the Helicity Drive Magneto-Inertial Fusion Concept

Abstract:

The Helicity Drive is a new, compact magneto-inertial fusion concept with a unique fusion output scalability that could simplify the challenge of achieving net fusion gain in short pulses. The concept exploits magnetic reconnection-heating of merging plectonemic plasmas with peristaltic magnetic compression to increase the fusion triple product. The project proposes to perform magnetohydrodynamic simulations with select kinetic simulations to investigate the plasma physics behind the concept. Our Request for Assistance is therefore complementary to our existing, separately funded, experimental effort to build a new proof-of-concept device in collaboration with academia and national laboratories. Together, the proposed simulation effort is critical to the company's ambition of building a robust development program for our new magneto-inertial fusion concept.

Co. PI: Dr. Setthivoine You

Co. e-mail: setthivoine.you@helicityspace.com

Laboratory: LANL

Lab PI: Dr. Hui Li, hli@lanl.gov





INFUSE 2021a, June 14, 2021

Company: Microsoft Corporation, DUNS: 081466849

Title: Improving Plasma Control Capabilities in Magnetically-Confined Tokamak Systems with

Transformer Neural Networks

Abstract:

The ongoing AI revolution in fundamental science offers multifarious new opportunities for application and further development of cutting-edge machine learning algorithms used in Microsoft products. In particular, the advanced AI-enabled deep learning disruption prediction capability developed at PPPL is being actively targeted in current R&D efforts at DOE's Princeton Plasma Physics Laboratory (PPPL) for implementation into plasma control capabilities in magnetically-confined tokamak experiments. This objective represents a great candidate for the proposed implementation of Microsoft's approach based on transformer neural networks to improve forward temporal projection algorithms that accurately predict dangerous disruption events encountered in thermonuclear tokamak plasmas which can in turn lead to important beneficial advances in real-time plasma control in advanced tokamak systems, including ITER.

Co. PI: Dr. Alexey Svyatkovskiy

Co. e-mail: alsvyatk@microsoft.com

Laboratory: PPPL

Lab PI: Dr. William Tang, tang@pppl.gov





INFUSE 2021a, June 14, 2021

Company: Renaissance Americas Inc., DUNS: 117506666

Title: Phase Diagram of Li-LiH,D,(T) Mixtures and Implications for Tritium Retention and Extraction

Abstract:

Solutions of Lithium and its hydrides are expected to exhibit isotopic effects that could facilitate the extraction of LiT (alone or lumped with LiD) from liquid walls and blankets. As a preliminary test of this new concept, we propose to measure the phase-diagram of Li-LiH,D and analytically infer from it the behavior of Li-LiD,T.

Co. PI: Dr. Francesco Volpe

Co. e-mail: fv@renaissancefusion.eu

Laboratory: SRNL

Lab PI: Dr James Klein, james.klein@srnl.doe.gov





INFUSE 2021a, June 14, 2021

Company: TAE Technologies, Inc, DUNS: 065262557

Title: Extending Operational Boundaries in the Advanced FRC

Abstract:

The 3D hybrid Particle-In-Cell code HYM will be used at PPPL to simulate the stability properties of realistic plasma equilibrium states in Advanced Field Reversed Configuration (FRC) plasmas. The study will include the effects of the large fast ion population that is present in Advanced FRC plasmas due to the use of neutral beam injection (NBI). On the C-2W experiment at TAE Technologies, Inc, it is found empirically that the fast ion contribution has a strong stabilizing effect, allowing a high temperature FRC plasma to be confined with parameters that would not be accessible to conventional FRCs, which are lacking NBI. Using the HYM code, initial value simulations will be performed to identify the mechanism behind the stabilization effects of the NBI. In particular, the effect of the fast ion population on mode growth rate, non-linear saturation, and possible mode coupling will be studied. Simulation results will be used to interpret C-2W results by detailed comparison of numerical and experimental phenomena. Simulations will also be used to explore the use of other external actuators for mitigation of instabilities. The resulting improved theoretical understanding of operational boundaries will be later used to make critical decisions in the conceptual design of a next-step Advanced FRC device that is currently being planned at TAE. In this public-private partnership, scientific contributions from the Department of Energy will directly accelerate progress toward the development of fusion energy in the private sector.

Co. PI: Dr. Sean Dettrick

Co. e-mail: sean@tae.com

Laboratory: PPPL

Lab PI: Dr Elena Belova, ebelova@pppl.gov





INFUSE 2020b, November 25, 2020

Company: Commonwealth Fusion Systems, DUNS: 117005109

Title: Time-Dependent Boundary Modeling to Inform Design of SPARC Diagnostic and Actuators

Abstract:

In order to inform near-term design and enable future advanced control, CFS is looking to obtain modeling of the time-dependent boundary plasma behavior it can expect in SPARC. This will be used to test plasma response to various actuator designs provided by CFS and as inputs to synthetic diagnostic modeling to inform design decisions. This activity requires laboratory assistance because of the complexity of performing boundary plasma simulation that can accurately capture plasma, neutrals and their dynamic, self-consistent behavior. This is not a present capability of CFS or a capability that is commercially available, but is one that DOE maintains and improves as part of its Fusion Energy Sciences mission.

Co. PI: Dr. Alex Creely

Co. e-mail: alex@cfs.energy

Laboratory: ORNL

Lab PI: Dr. Jeremy Lore, lorejd@ornl.gov





INFUSE 2020b, November 25, 2020

Company: General Fusion Corp., DUNS: 117111477

Title: Ion Temperature Diagnostic Improvement

Abstract:

This project is to improve General Fusion's ion temperature diagnostic for fusion plasmas. An accurate, time- and spatially-resolved measurement of ion temperature will enable experimental confirmation of fusion reaction rates.

Co. PI: Dr. Akbar Rohollahi

Co. e-mail: Akbar.Rohollahi@generalfusion.com

Laboratory: ORNL

Lab PI: Dr. Theodore Biewer, biewertm@ornl.gov





INFUSE 2020b, November 25, 2020

Company: Princeton Fusion Systems, LLC, DUNS: 0020074970

Title: Magnetic Field Vector Measurements Using Doppler-Free Saturation Spectroscopy

Abstract:

A non-perturbative diagnostic will be deployed to measure the topology of the equilibrium magnetic field in the PFRC-2 device at PPPL. The diagnostic implements Doppler-free saturation spectroscopy to obtain a 2D high-resolution, spatially resolved, measurement of the H_{α} spectral line profile.

Co. PI: Dr. Charles Swanson

Co. e-mail: charles.swanson@psatellite.com

Laboratory: PPPL

Lab PI: Dr. Samuel Cohen, scohen@pppl.gov





INFUSE 2020b, November 25, 2020

Company: Magneto Inertial Fusion Technologies, Inc, DUNS: 065262557

Title: Staged Z-pinch modeling with HYDRA and CHICAGO codes

Abstract:

The Staged Z-pinch (SZP) fusion concept is a magneto-inertial compression scheme where small amounts of fusion fuel (pure deuterium gas, or a mixture of deuterium and tritium gas) are brought to fusion relevant conditions by passing multi-million amperes strong current through a cylindrical shell of high atomic number material. Modeling with the MACH2 code suggests that net fusion energy gain can be achieved when currents in the 10 million amperes range compress a 50%-50% mixture of deuterium and tritium gas. In this project various SZP configurations will be explored with the HYDRA and CHICAGO codes through collaboration with the Lawrence Livermore National Laboratory. HYDRA is a radiation-magnetohydrodynamic code, similar to MACH2, while CHICAGO is a particle-in-cell code which is suitable for a more realistic treatment of the alpha particle heating. Of particular interest are models for high current machines. The ultimate project goal is to provide independent confirmation of net fusion energy gain from the Staged Z-pinch.

Co. PI: Dr. Hafiz Rahman

Co. e-mail: hafiz@miftec.com

Laboratory: LLNL

Lab PI: Dr. Drew Higginson, higginson2@llnl.gov





INFUSE 2020b, November 25, 2020

Company: Renaissance Americas, Inc, DUNS: 065262557

Title: Innovative Joints for High-Temperature Superconducting Tapes

Abstract:

The ability to segment HTS coils for tokamaks and stellarators is very attractive but requires joints of ultra-low resistance, well below 1 nOhm. These could be enabled by ultra-thin In-Ag solder (at BNL) between ad-hoc HTS splices (from U. Houston).

Co. PI: Dr. Francesco Volpe

Co. e-mail: fv@renaissancefusion.eu

Laboratory: BNL

Lab PI: Dr. Bill Sampson, wsampson@bnl.gov





INFUSE 2020b, November 25, 2020

Company: TAE Technologies, DUNS: 065262557

Title: Measurement of Magnetic Field using Doppler-Free Saturation Spectroscopy (DFSS) in C-2W FRC

plasma

Abstract:

In TAE Technologies' fusion approach, which requires high population of confined fast ions, Field Reversed Configuration (FRC) plasma provides an advantage due its unique magnetic field profile. In the experiment, measurement of internal magnetic field profile is important to verify the presence of the FRC and to estimate/simulate the orbit of confined fast ions. Doppler-Free Saturation Spectroscopy (DFSS) is capable of measuring Zeeman and Stark splitting with a resolution nearly three orders of magnitude when compared to conventional OES capabilities, and hence serve as excellent non-perturbative diagnostic to measure a low magnetic field.

A feasibility study conducted by ORNL in collaboration with TAE Technologies has shown that measurements of magnetic fields with an error of ± 5 Gauss may be possible to obtain in C-2W FRC plasma. In this proposal, ORNL will temporarily deploy their mobile Doppler Free Saturation Spectroscopy (DFSS) diagnostic system on TAE's C-2W FRC plasma device. ORNL will also help with the operation and data analysis of DFSS system on C-2W. The main goals of this collaboration are:

- 1) Validate that adequate signal-to-noise ratio (SNR) as well as temporal and spatial resolution can be achieved with DFSS in C-2W plasma.
- 2) Demonstrate the capability of DFSS to non-intrusively measure low magnetic fields and its direction in the core of the FRC plasma.
- 3) Experimentally assess the presence of a reversed magnetic field configuration inside the C-2W plasma.

Co. PI: Dr. Deepak Gupta

Co. e-mail: dgupta@tae.com

Laboratory: ORNL

Lab PI: Dr. Elijah Martin, martineh@ornl.gov





INFUSE 2020b, November 25, 2020

Company: TAE Technologies, DUNS: 065262557

Title: Feasibility Study of High-Flux FRC Formation via Spheromak Merging for C-2W Experiments

Abstract:

This project on MRX at PPPL will allow us to assess the feasibility of new spheromak-merging high magnetic-flux FRC formation technique for C-2W NBI experiment at TAE that could further advance C-2W performance to achieve higher energy density regime.

Co. PI: Dr. Hiroshi Gota

Co. e-mail: hgota@tae.com

Laboratory: PPPL

Lab PI: Dr. Masaaki Yamada, myamada@pppl.gov





INFUSE 2020b, November 25, 2020

Company: Tokamak Energy, Inc., DUNS: 117135313

Title: XGC1 predictions of Scrape of Layer width in present and future high field spherical tokamaks

Abstract:

This project aims to calculate the Scrape-Off-Layer width and the heat power deposition of present and future high field spherical tokamak reactors using the global gyrokinetic code XGC1 developed at PPPL.

Co. PI: Dr. Michelle Romanelli

Co. e-mail: Michele.Romanelli@tokamakenergy.co.uk

Laboratory: PPPL

Lab PI: Dr. Choonseok Chang, cschang@pppl.gov





INFUSE 2020b, November 25, 2020

Company: Tokamak Energy, Inc., DUNS: 117135313

Title: Fabrication and characterization of transition metal hydrides for radiation shielding in tokamak

devices

Abstract:

Metal hydrides are identified as key radiation shielding materials to protect components in tokamak reactors. This project will investigate the fabrication and characterization of metal hydrides manufactured by the powder metallurgy process.

Co. PI: Dr. Thomas Davis

Co. e-mail: tom.davis@tokamakenergy.co.uk

Laboratory: LANL

Lab PI: Dr. Caitlin Taylor, caitlin@lanl.gov





INFUSE 2020b, November 25, 2020

Company: Type One Energy Group, Inc., DUNS: 117135313

Title: Characterization and Qualification of JK2LB Alloy for Additive Manufacturing of Fusion

Components

Abstract:

JK2LB is a nuclear alloy providing fast clearance for fusion components. The project provides initial characterization & qualification of JK2LB for additive manufacturing (AM). The ORNL High Flux Isotope Reactor will irradiate AM-JK2LB specimens followed by tensile & microstructural analysis.

Co. PI: Mr. Randall Volberg

Co. e-mail: rvolberg@typeoneenergy.com

Laboratory: ORNL

Lab PI: Dr Yutai Katoh, katohy@ornl.gov





INFUSE 2020a, August 14, 2020

Company: Commonwealth Fusion Systems, DUNS: 117005109

Title: Baselining a Tritium Accountancy and Safety Case for a Molten Salt Liquid Immersion Fusion

Blanket

Abstract:

The ARC reactor concept is a leading commercial fusion plant concept, featuring a simplified reactor design and decreased costs

The switch to high temperature superconducting (HTS) magnets further enables innovation in the reactor's blanket. Since the power density may be too high for solid ceramic breeders, and the high magnetic field may create unacceptably large pressure drops in liquid metal breeders, the molten salt FLiBe (2LiF+BeF2) has been proposed as a tritium breeder, multiplier, and coolant for ARC.

Any economically and environmentally viable fusion reactor must minimize onsite tritium inventories and environmental releases (to \lesssim 0.1 g tritium released annually) and successfully mitigate release of tritium and activation products during off-normal events or accidents. While tritium transport and accident analyses are routinely performed by Idaho National Laboratory for Fusion Energy Systems Studies (FESS) designs such as ARIES and FNSF, no comparable analyses have ever been performed for ARC or another design using FLiBe. We propose to leverage the expertise of INL researchers and the MELCOR/TMAP code developed there to perform these analyses for ARC, in order to characterize its tritium transport and safety behavior.

Co. PI: Dr. Brandon Sorbom

Co. POC: brandon@cfs.energy

Laboratory: INL

Lab PI: Dr. Paul Humrickhouse, Paul.Humrickhouse@inl.gov





INFUSE 2020a, August 14, 2020

Company: Commonwealth Fusion Systems, DUNS: 117005109

Title: SPARC 3D Field Physics and Support of the Non-Axisymmetric Coil Assessment

Abstract:

The Ideal Perturbed Equilibrium Code (IPEC) code developed and maintained by Princeton Plasma Physics Laboratory Scientists Jong-Kyu Park and Nikolas Logan has revolutionized the physical understanding of plasma sensitivity to error fields and is the centerstone of this proposal. IPEC will be used to assess the types of error fields that the plasma is most susceptible to in the various plasma conditions expected during SPARC plasma current ramp-up, the steady equilibrium phase, and the plasma current ramp-down. Knowledge of the dominant error fields then allows the evaluation of a set of error field correction coils where the metric is the overlap of the applied correction field with the dominant spectrum.

Co. PI: Dr. Alex Creely

Co. POC: alex@cfs.energy

Laboratory: PPPL transferred to LLNL

Lab PI: Dr. Nikolas Logan, logan35@llnl.gov





INFUSE 2020a, August 14, 2020

Company: Commonwealth Fusion Systems, DUNS: 117005109

Title: Advanced Manufacturing Workflows for Tokamak Internal Components

Abstract:

CFS is currently designing a commercial fusion reactor called ARC, whose key innovation is the use of high-field HTS magnets. These allow for reduced plant size and cost. In addition, they allow for resistive, demountable superconducting joints that give ready access to interior components, dramatically improving RAMI. In order to fully realize benefits of demountability, the following challenges must be addressed:

- A rapid/inexpensive fabrication method must be developed to keep costs down of replacing the internal components
- The fabrication method must be able to support the construction of large (several meter scale) components

In addition, early fusion energy devices will have a learning curve and there will likely be design changes to internal components. This may require expensive re-tooling unless we have an adaptable/reconfigurable fabrication method. Additive manufacturing (AM) is a potential solution to the above challenges and opens up the rapid, low cost fabrication of large components with novel materials. The metal Big Area Additive Manufacturing team developed GMAW-based (gas-metal-arc-welding) capability at ORNL from the ground up. Our overall objective is to design a workflow for the design and manufacture of an AM internal component in a fusion device. This workflow will be tested and driven by the production of an actual subscale divertor module of an ARC vacuum vessel

Co. PI: Dr. Brandon Sorbom

Co. POC: brandon@cfs.energy

Laboratory: ORNL

Lab PI: Dr. Andrzej Nycz, nycza@ornl.gov





INFUSE 2020a, August 14, 2020

[RESCINDED]

Company: Gamma Alloys, Inc., DUNS: 830224049

Title: Tungsten Engineered Feed Stock for PFCs

Abstract:

Gamma would seek to work with Oak Ridge National Lab for reasons as follows. ORNL has extensive knowledge in process modeling, process control, in-situ and ex-situ characterization of a wide range of high temperature materials fabricated via additively manufacturing. This includes fabrication of refractory materials such as Tungsten and Molybdenum. While ORNL has exhibited success in printing these systems, the process window range is relatively small. Besides porosity, which can largely be controlled via the energy density, the major technical challenge is in suppressing the formation of intergranular cracks along columnar grains generating during printing. Prior research has shown that powders decorated with small particles can induce the nucleation of equiaxed grains during solidification. By manipulating the solidification dynamics, it may be possible to eliminate columnar grains and therefore minimize cracking. Furthermore, as traditional processing of refractory materials is incredibly difficult, processing via additive manufacturing offers a novel opportunity to surpass the current manufacturing bottleneck and deploy these materials into industrial use. Currently, Gamma is in the early stages of a, AM Aluminum CRADA with ORNL focusing on similar development for Aluminum engineered feedstock. Lastly ORNL is our ideal choice as there is an internal need for Tungsten & Tungsten alloy parts & printing.

Co. PI: Mr. Micah Peabody

Co. POC: micah.peabody@gammaalloys.com

Laboratory: ORNL

Lab PI: Dr. Peeyush Nandwana, nandwanap@ornl.gov





INFUSE 2020a, August 14, 2020

Company: General Fusion Corp., DUNS: 117111477

Title: Advanced Stability Analysis for Magnetized Target Fusion

Abstract:

This project seeks to apply advanced computational stability analyses to model equilibrium states representing the Fusion Demonstration Plant (FDP) device General Fusion is designing. The FDP is a Magnetized Target Fusion concept that strongly compresses a toroidal plasma inside of a liquid Lithium blanket. In particular, building on encouraging initial analyses, the effect of plasma rotation on the stability will be studied using the Resistive DCON and MARS-F codes under development at Princeton Plasma Physics Laboratory. The results will help to inform General Fusion on the stable operation of their design, and the project will pave the way for more advanced analyses such as the influence the energetic particles driven from fusion reactions would have on the stability.

Co. PI: Dr. Aaron Froese

Co. POC: aaron.froese@generalfusion.com

Laboratory: PPPL

Lab PI: Dr. Zhirui Wang, zwang@pppl.gov





INFUSE 2020a, August 14, 2020

Company: Solid Material Solutions, LLC, DUNS: 0020074970

Title: Low Temperature Testing of New Lower Cost Magnum-NX HTS Cable for Fusion

Abstract:

This program will directly measure the electrical current carrying properties of a new type of lower cost, more robust and quench resistant high temperature superconducting tape cable, thereby providing vital information for designing and developing fusion reactor coils and assessing their utility. The test cables will be produced by Solid Material Solutions, LLC and testing will be completed by staff at Brookhaven National Laboratory.

Co. PI: Dr. Alexander Otto

Co. POC: alex.otto@solidmaterialsolutions.com

Laboratory: BNL

Lab PI: Dr. Ramesh Gupta, qupta@bnl.gov





INFUSE 2020a, August 14, 2020

Company: TAE Technologies, DUNS: 065262557

Title: Development of phased-array HHFW antenna and load-resilient matching network for the C-2W

FRC plasma device

Abstract:

This proposal is to develop the optimized design of a high power capable phased-array HHFW antenna and a load-resilient matching network for the C-2W FRC plasma device. The antenna will be designed to allow arbitrary phasing of currents on the radiating elements in order to maximize heating efficiency. It will be necessary to minimize RF/edge plasma interactions with design features to be considered including low-Z insulating limiters and the reduction to the greatest possible extent of surface currents on the antenna enclosure. The matching network design will incorporate a passive load-resilience feature, which will allow the antenna to operate with arbitrary current phasing between elements, even for low levels of antenna coupling for which impedance matching of all elements would otherwise not be possible.

Co. PI: Dr. Xiaokang Yang

Co. POC: xyang@tae.com

Laboratory: ORNL

Lab PI: Dr. Richard Goulding, gouldingrh@ornl.gov





INFUSE 2020a, August 14, 2020

Company: Tokamak Energy, Inc., DUNS: 117135313

Title: Investigating microstability characteristics of next step tokamaks across a range of aspect ratios

Abstract:

This project will investigate the microstability characteristics of next step tokamaks across arrange of aspect ratios. A systems code followed by a 1.5D transport code will be used to produce plasma equilibria and kinetic profiles that satisfy a set of high-level criteria across a range of aspect ratios. Linear gyrokinetic simulations will then be used to characterise the strength and thresholds of micro-instabilities to identify which configurations are most likely to project to high confinement. The results from this project are expected to provide assistance to Tokamak Energy by providing valuable insight to the design of the Company's next step device, ST-F1, and by informing the research programme on Tokamak Energy's high field spherical tokamak, ST40.

Co. PI: Dr. Steven McNamara

Co. POC: Steven.Mcnamara@tokamakenergy.co.uk

Laboratory: PPPL

Lab PI: Dr. Walter Guttenfelder, wgutten@pppl.gov





INFUSE 2020a, August 14, 2020

Company: Tokamak Energy, Inc., DUNS: 117135313

Title: Development of an RF Antenna to start-up and sustain a fusion plasma in a spherical tokamak

Abstract:

The central solenoid is an intrinsic part of all present-day tokamaks and most spherical tokamaks (ST). The use of a conventional solenoid in an ST-based fusion reactor may be impossible. Solenoid-free plasma start-up and steady state operation is therefore an area of extensive worldwide research activity.

Tokamak Energy's ST40 has a toroidal magnetic field of 3T which allows testing of reactor relevant RF based plasma start-up, current ramp-up and sustainment methods with commercially available MW range RF power sources. Electron Bernstein wave (EBW) based plasma start-up and plasma current drive are in the research programme of ST40. Efficient EBW excitation in the plasma requires RF power to be launched as an X-mode from the high field side (HFS) of the machine. HFS RF launching was always technically difficult in tokamaks but it is even more challenging in STs because of very limited space at the centre of the torus. However, it is strategically important to develop a technology for HFS RF launching in the STs.

Oak Ridge National Laboratory (ORNL) will perform a conceptual design of an ST compatible HFS launching system to enable investigation of a reactor scale plasma start-up, current ramp-up and sustainment of spherical tokamak plasms, The ultimate aim will be to demonstrate steady-state EBW operation and eventually to use EBW as a main method of plasma current generation in an ST reactor.

Co. PI: Dr. Vladimir Shevchenko

Co. POC: vladimir.shevchenko@tokamakenergy.co.uk

Laboratory: ORNL

Lab PI: Dr. Tim Bigelow, bigelowts@ornl.gov





INFUSE 2020a, August 14, 2020

Company: Tokamak Energy, Inc., DUNS: 117135313

Title: Conceptual design of a tritium pellet injector for the ST40 spherical tokamak

Abstract:

ORNL has a long track record of pellet injection technology development. For the application of pellet fueling on ST40, a previous design by ORNL of a flexible pipe-gun type injector named "pellet injector in a suitcase" would likely be an ideal technology to use as it has already been proven on several fusion devices and can be built and integrated into ST40 for relatively modest cost. The application of this system for ST40 would require some changes to make it tritium compatible and provide the necessary isolation of tritium containing components. The implementation of the injector for tritium use is of research interest to ORNL who have yet to deploy an injection system for use with tritium. The present proposal is to determine the pellet sizes to be utilized on ST40 and to modify the design for these sizes and for tritium compatibility.

Co. PI: Mr. David Wilson

Co. POC: david.wilson@tokamakenergy.co.uk

Laboratory: ORNL

Lab PI: Dr Larry Baylor, baylorlr@ornl.gov





INFUSE 2019b, September 23, 2019

Company: Advanced Conductor Technologies, DUNS: 969353734

Title: Development of a modeling toolbox for CORC® cable performance evaluation

Abstract:

Advanced Conductor Technologies and SuperPower Inc. request Lawrence Berkeley National Laboratory (LBNL) to develop a simulative tool that would create a deeper understanding of current distribution between tapes in CORC® cables for fusion magnet in the presence of common performance variations within REBCO tapes when operating at high magnetic fields. Such tool, which would be developed under the "Enabling technologies including new and improved magnets" topic area, would allow tailoring the design of CORC® cables for fusion magnets based on actual REBCO tape performance variations to ensure their optimum operation and prevent conductor burnout during a magnet quench. The model should be based on actual REBCO tape performance, with emphasis on variations in high-field REBCO tape performance due to variations in chemistry and processing conditions, and other key parameters such as contact resistance between REBCO tapes in CORC® cables.

Co. PI: Dr. Danko Van der Laan

Co. POC: danko@advancedconductor.com

Laboratory: LBNL

Lab PI: Dr. Steven Gourlay, sagourlay@lbl.gov





INFUSE 2019b, September 23, 2019

Company: Commonwealth Fusion Systems, DUNS: 117005109

Title: Superconducting Cable Quench Detection

Abstract:

This proposal will enable Commonwealth Fusion Systems (CFS) to pursue its cable development program by using the 10-T Brookhaven National Laboratory (BNL) dipole magnet, DCC017. CFS and BNL will work together on cable design and construction, cable instrumentation, design and construction of a cable test fixture, quench testing at 4 K temperatures, and quench data analysis.

Co. PI: Dr. Brandon Sorbom

Co. POC: brandon@cfs.energy

Laboratory: BNL

Lab PI: Dr. Ramesh Gupta, gupta@bnl.gov





INFUSE 2019b, September 23, 2019

Company: Commonwealth Fusion Systems, DUNS: 117005109

Title: Divertor Component Testing

Abstract:

Power exhaust is an immense challenge in tokamaks. Commonwealth Fusion Systems (CFS), in collaboration with MIT and others, is designing and building a compact, high-field tokamak for the demonstration of net fusion energy, called SPARC. A successful SPARC divertor will require very carefully engineered and qualified divertor tiles and cassettes to handle the cyclic thermal loading. Testing of materials and components under relevant heat flux conditions is a necessary step for developing a robust and reliable power exhaust system. Here we propose to use the high-heat flux testing expertise maintained by ORNL, used in support of NSTX-U, to demonstrate the thermal performance of tungsten-coated graphitic foam targets, to help CFS and its collaborators assess the performance of base materials and divertor mockups under SPARC-like divertor heat flux conditions.

Co. PI: Dr. Dan Brunner

Co. POC: dan@cfs.energy

Laboratory: ORNL

Lab PI: Dr. Travis Gray, tkgray@pppl.gov





INFUSE 2019b, September 23, 2019

Company: Commonwealth Fusion Systems, DUNS: 117005109

Title: Divertor Plasma Simulations

Abstract:

Power exhaust is an immense and unsolved challenge in tokamaks. The intensity of the boundary plasma in present experiments falls far short of the conditions expected in net-energy tokamaks. This proposal will allow CFS to use the unique UEDGE plasma neutral simulation code to simulate boundary plasmas under conditions relevant to its net-energy tokamak device, called SPARC.

Co. PI: Dr. Dan Brunner

Co. POC: dan@cfs.energy

Laboratory: LLNL

Lab PI: Dr. Maxim Umansky, umansky1@llnl.gov





INFUSE 2019b, September 23, 2019

Company: Commonwealth Fusion Systems., DUNS: 117005109

Title: Alpha Particle Diagnostics Simulation

Abstract:

Measuring and understanding the physics of transport of fast ions is an important part of the missions of TFTR, JET, ITER and SPARC, because it affects both plasma performance (MHD stability and plasma heating) and survival of the first wall. A well-designed diagnostic set will be required to study the transport and loss of energetic ions from both classical (ripple) and MHD-driven mechanisms. Careful simulations of the expected properties of the energetic ion populations must first be carried out to optimally design, and position the diagnostics that are required to adequately test the transport models. The work proposed here aims to lay out the requirements for alpha-particle diagnostics, especially lost alphas, by predicting how these particles are expected to behave under conditions relevant to SPARC, CFS' break-even tokamak. We propose to use two sets of code developed and maintained by the Princeton Plasma Physics Laboratory to perform calculations of fast-ion losses in SPARC arising from toroidal field (TF) ripple and magnetohydrodynamic effects.

Co. PI: Dr. Steve Scott

Co. POC: sscott@psfc.mit.edu

Laboratory: PPPL

Lab PI: Dr. Gerrit Kramer and Dr. Mario Podesta, mpodesta@pppl.gov





INFUSE 2019b, September 23, 2019

[RESCINDED]

Company: HelicitySpace, DUNS: 117087016

Title: Development of a High-Current Solid-State Switch for Magneto-Inertial Fusion

Abstract:

Magneto-inertial fusion attempts to satisfy the Lawson criterion in short pulses of the order of plasma energy confinement times. The power systems for this class of fusion concepts generally require large (> 1 MA) level currents delivered very rapidly. Delivering electricity to the grid will then require high frequency pulses (~ 1 Hz). There is therefore a strong need for switches capable of satisfying these requirements. The project proposes to develop power stacks capable of scaling up to these requirements based on light-activated thyristors that promise to provide more compact, robust and scalable switches for magneto-inertial fusion concepts.

Co. PI: Dr. Setthivoine You

Co. POC: <u>setthivoine.you@helicityspace.com</u>

Laboratory: PPPL

Lab PI: Mr. Clement Bovet, cbovet@pppl.gov





INFUSE 2019b, September 23, 2019

Company: HelicitySpace, DUNS: 117087016

Title: Simulation of Plectoneme Formation

Abstract:

Plectonemes are non-axisymmetric Taylor states recently discovered in the SSX and MOCHI experiments. These experiments have observed remarkable stability and long lifetimes, without close-fitting walls in some cases, despite their non-axisymmetric nature. The Helicity Drive is an innovative fusion energy concept that exploits these properties together with magnetic reconnection heating and passive magnetic compression to achieve triple products sufficient for net energy gain. The company has detailed physics calculations that estimate the scaling of plasma parameters and triple product with input parameters based on prior laboratory experience. This project proposes to perform high-performance 3D MHD numerical simulations of the formation process of plectonemes to improve the understanding of the SSX and MOCHI results, and help enable predictive capabilities for the Helicity Drive concept.

Co. PI: Dr. Setthivoine You

Co. POC: setthivoine.you@helicityspace.com

Laboratory: LANL

Lab PI: Dr. Hui Li, hli@lanl.gov





INFUSE 2019b, September 23, 2019

Company: Hyperjet Fusion Corp., DUNS: 080736078

Title: 3D MHD Simulations Support for PJMIF

Abstract:

We are looking for help from the national labs in conducting credible 3D MHD simulations of our proposed target formation approach, assessing relevant merging conditions of the compact toroids that can be created in the near term and to assess the magnetic topology and plasma properties that can be obtained. These simulations are challenging because they require the study of a complicated magnetic topology in 3D, varying over a wide range of physical length scales as the compact toroids converge and stagnate, and have proved well beyond the capabilities of codes we have been able to access in the commercial space.

Co. PI: Dr. Franklin Witherspoon

Co. POC: witherspoon@hyperjetfusion.com

Laboratory: LANL

Lab PI: Dr. Glen Wurden and/or Dr. Samuel Langendorf, samuel.langendorf@lanl.gov





INFUSE 2019b, September 23, 2019

Company: TAE Technologies, Inc., DUNS: 065262557

Title: Simulations of Global Stability in the C-2W Device

Abstract:

TAE Technologies, Inc, proposes to use the HYM 3D particle-in-cell code developed at PPPL to study the synergistic effects of neutral beam injection and end biasing on the global stability of FRC plasmas in conditions relevant to the C-2W experimental device and the planned next-step device, Copernicus.

Co. PI: Dr. Sean Dettrick

Co. POC: sean@tae.com

Laboratory: PPPL

Lab PI: Dr Elena Belova, ebelova@pppl.gov





INFUSE 2019b, September 23, 2019

Company: TAE Technologies, Inc., DUNS: 065262557

Title: Doppler-Free Saturation Spectroscopy (DFSS) for Magnetic and Electric Field Measurements in an

FRC plasma

Abstract:

The proposal will examine the feasibility of implementing Doppler Free Saturation Spectroscopy (DFSS) to measure the magnetic and electric fields profiles in the Field Reversed Configuration (FRC) plasma of TAE's C-2W device. There are two primary objectives,

1) An error analysis will be conducted to determine the minimum magnetic and electric field that can be determined by DFSS, and measurement uncertainty as a function of magnetic and electric field magnitude and direction. Potential sources of systematic error will be identified using C-2W plasma parameters.

2) Recommend preliminary design for the DFSS system based on C-2W machine parameters, accessibility, and the desired spatial and temporal resolution.

Co. PI: Dr. Deepak Gupta

Co. POC: dgupta@tae.com

Laboratory: ORNL

Lab PI: Dr. Elijah Martin, martineh@ornl.gov





INFUSE 2019b, September 23, 2019

Company: TAE Technologies, Inc., DUNS: 065262557

Title: Developing high harmonic fast wave (HHFW) as an enabling electron heating actuator for an FRC

plasma

Abstract:

The main task of this project is to perform HHFW simulations in FRC plasma by using Petra-M code and the 4-strap antenna geometry implemented in LArge Plasma Device (LAPD) under different plasma conditions, for example, at (1) the different phasing between straps, (2) the different external magnetic field (thus different RF frequency), and (3) the different antenna radial position. Furthermore, due to compact and limited space near the midplane of C-2W, the impact of the different number of antenna straps will be also explored in order to improve the antenna design and its performance. A study of high power enabling HHFW antenna design will be considered using the HHFW engineering and simulation tools developed at PPPL.

A possible verification activity with the experimental data (RF wave magnetic fields at both the near and far field measured by B-dot magnetic probes) for the HHFW phased-array (4-strap) antenna in LAPD will be also considered.

Co. PI: Dr. Xiaokang Yang

Co. POC: xyang@tae.com

Laboratory: PPPL

Lab PI: Dr. Nicola Bertelli, nbertell@pppl.gov

